390-012
Splash-Proof EMI/RFI Cable Sealing Backshell
Light-Duty with Strain Relief
Type C - Direct Coupling - Low Profile

CONNECTOR DESIGNATORS
A-B*-C-D-E-F
G-H-J-K-L-S

*** Conn. Desig. B See Note 5**

DIRECT COUPLING



TYPE C OVERALL SHIELD TERMINATION



STYLE 2 (STRAIGHT See Note 1)







STYLE L
Light Duty
(Table V)



STYLE G
Light Duty
(Table V)



© 2005 Glenair, Inc.

TABLE III: FRONT ADAPTER

Shell Size	J Max - Conn. Designator A-E-F J-H-L-S	D-B-G-K	C
08/09	1.180 (30.0)	1.440 (36.6)	
10/11	1.180 (30.0)	1.440 (36.6)	
12/13	1.180 (30.0)	1.440 (36.6)	1.735 (44.1)
14/15	1.180 (30.0)	1.440 (36.6)	1.915 (48.6)
16/17	1.380 (35.0)	1.560 (39.6)	1.915 (48.6)
18/19	1.380 (35.0)	1.560 (39.6)	1.915 (48.6)
20/21	1.380 (35.0)	1.560 (39.6)	1.915 (48.6)
22/23	1.380 (35.0)	1.560 (39.6)	1.915 (48.6)
24/25	1.380 (35.0)	1.560 (39.6)	1.915 (48.6)
28/29	1.610 (40.9)	1.560 (39.6)	1.915 (48.6)
32/33	1.610 (40.9)	1.750 (44.5)	1.915 (48.6)
36	1.610 (40.9)	1.750 (44.5)	1.915 (48.6)
40	1.610 (40.9)	2.190 (55.6)	1.915 (48.6)

See inside back cover fold-out or pages 13 and 14 for Tables I and II.

1. When maximum cable entry (page 22) is exceeded, Style 2 will be supplied. (Function S only).
2. Metric dimensions (mm) are indicated in parentheses.
3. Cable range is defined as the accommodations range for the wire bundle or cable. Dimensions shown are not intended for inspection criteria.
4. Consult factory for shorter lengths on straight backshells.
5. When using Connector Designator B refer to pages 18 and 19 for part number development.

TABLE IV: CABLE ENTRY

Elbow Size	E Max		F Max		G Max		H Max	
01	.457	(11.6)	1.700	(43.2)	.636	(16.2)	1.698	(43.1)
02	.457	(11.6)	1.700	(43.2)	.636	(16.2)	1.698	(43.1)
03	.630	(16.0)	1.748	(44.4)	.709	(18.0)	1.818	(46.2)
04	.692	(17.6)	1.808	(45.9)	.734	(18.6)	1.838	(46.7)
05	.755	(19.2)	1.898	(48.2)	.825	(21.0)	1.908	(48.5)
06	.848	(21.5)	1.998	(50.7)	.990	(25.1)	1.998	(50.7)
07	1.036	(26.3)	2.198	(55.8)	1.090	(27.7)	2.168	(55.1)
08	1.130	(28.7)	2.338	(59.4)	1.325	(33.7)	2.278	(57.9)
09	1.130	(28.7)	2.338	(59.4)	1.325	(33.7)	2.278	(57.9)
10	1.130	(28.7)	2.338	(59.4)	1.325	(33.7)	2.278	(57.9)

TABLE V: CABLE ENTRY

Dash No.	K Max		L Max		Cable Range Min		Cable Range Max	
01	.781	(19.8)	.593	(15.1)	.062	(1.6)	.125	(3.2)
02	.968	(24.6)	.718	(18.2)	.125	(3.2)	.250	(6.4)
03	1.046	(26.6)	.843	(21.4)	.250	(6.4)	.375	(9.5)
04	1.156	(29.4)	.968	(24.6)	.375	(9.5)	.500	(12.7)
05	1.218	(30.9)	1.109	(28.2)	.500	(12.7)	.625	(15.9)
06	1.343	(34.1)	1.218	(30.9)	.625	(15.9)	.750	(19.1)
07	1.468	(37.3)	1.343	(34.1)	.750	(19.1)	.875	(22.2)
08	1.593	(40.5)	1.468	(37.3)	.875	(22.2)	1.000	(25.4)
09	1.718	(43.6)	1.593	(40.5)	1.000	(25.4)	1.125	(28.6)
10	1.843	(46.8)	1.718	(43.6)	1.125	(28.6)	1.250	(31.8)

© 2005 Glenair, Inc.