



0355



0355-0-15-XX-02-XX-10-0

Solder mount in 2,59 min. mounting hole


0354



0354-0-15-XX-02-XX-10-0

Pentagonal press-fit in 2,64 min. plated thru hole


3490



3490-0-15-XX-02-XX-10-0

Press-fit in 2,31 mounting hole


3808



3808-0-15-XX-02-XX-10-0

Press-fit in 2,29 mounting hole


9184



9184-0-15-XX-02-XX-40-0


Bottom entry, surface mount
2,34 min. plated thru hole.
Also available on carrier tape,
Order as: 9184-0-57-XX-02-XX-40-0

9222



9222-2-15-XX-02-XX-40-0

Bottom entry, surface mount
2,08 min. plated thru hole
Also available on carrier tape,
Order as: 9222-2-57-XX-02-XX-40-0



Carrier tape format for
9184 & 9222.
1,500 pieces per 330mm reel

SPECIFICATIONS

SHELL MATERIAL:
Brass Alloy 360, 1/2 Hard

CONTACT MATERIAL:
Beryllium Copper Alloy 172, HT

DIMENSION IN INCHES
TOLERANCES ON:
LENGTHS: $\pm 0,13$
DIAMETERS: $\pm 0,05$
ANGLES: $\pm 2^\circ$

ORDER CODE: XXXX - X - 15 - XX - 02 - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,08 μ m TIN/LEAD OVER NICKEL
- ◇ 80 5,08 μ m TIN OVER NICKEL (RoHS)
- ◇ 15 0,25 μ m GOLD OVER NICKEL (RoHS)



SPECIFY CONTACT FINISH:

- 01 5,08 μ m TIN/LEAD OVER NICKEL
- ◇ 80 5,08 μ m TIN OVER NICKEL (RoHS)
- ◇ 27 0,76 μ m GOLD OVER NICKEL (RoHS)

CONTACT

#02 CONTACT (DATA ON PAGE 225)