


UZS 4.5mmL Chip Type



- Chip type with 4.5mm height.
- Designed for surface mounting on high density PC board.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU, (EU)2015/863).
- AEC-Q200 compliant. Please contact us for details.



Specifications

| Item | Performance Characteristics | | | | | | | |
|-------------------------------|---|---|-----|----|----|----|----|----|
| Category Temperature Range | -40 to +85°C | | | | | | | |
| Rated Voltage Range | 4 to 50V | | | | | | | |
| Rated Capacitance Range | 1 to 220μF | | | | | | | |
| Capacitance Tolerance | +20% at 120Hz, 20°C | | | | | | | |
| Leakage Current | After 2 minutes' application of rated voltage at 20°C, leakage current is not more than 0.01 CV or 3 (μA), whichever is greater. | | | | | | | |
| Tangent of loss angle (tan δ) | Measurement frequency : 120Hz at 20°C | | | | | | | |
| | Rated voltage (V) | 4 | 6.3 | 10 | 16 | 25 | 35 | 50 |
| Stability at Low Temperature | Measurement frequency : 120Hz | | | | | | | |
| | Rated voltage (V) | 4 | 6.3 | 10 | 16 | 25 | 35 | 50 |
| | Impedance ratio ZT / Z20 (MAX.) | Z-25°C / Z+20°C | 7 | 4 | 3 | 2 | 2 | 2 |
| Endurance | The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 2000 hours at 85°C. | | | | | | | |
| | Capacitance change | Within ±20% of the initial capacitance value | | | | | | |
| | tan δ | 200% or less than the initial specified value | | | | | | |
| Shelf Life | The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 2000 hours at 85°C. | | | | | | | |
| | Capacitance change | Within ±10% of the initial capacitance value | | | | | | |
| | tan δ | Less than or equal to the initial specified value | | | | | | |
| Resistance to soldering heat | The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C. | | | | | | | |
| | Capacitance change | Within ±10% of the initial capacitance value | | | | | | |
| | Leakage current | Less than or equal to the initial specified value | | | | | | |
| Marking | Black print on the case top. | | | | | | | |

Chip Type



Type numbering system (Example : 16V 10μF)



Dimensions

| Cap. (μF) | Code | 4 | | 6.3 | | 10 | | 16 | | 25 | | 35 | | 50 | |
|-----------|------|-----|----|-----|----|-----|----|-----|-----|-----|-----|----|----|-----|-----|
| | | 0G | 0J | 1A | 1C | 1E | 1V | 1H | | | | | | | |
| 1 | 010 | | | | | | | | | | | | | 4 | 8.4 |
| 2.2 | 2R2 | | | | | | | | | | | | | 4 | 13 |
| 3.3 | 3R3 | | | | | | | | | | | | | 4 | 17 |
| 4.7 | 4R7 | | | | | | | | | | | | | 5 | 20 |
| 10 | 100 | | | | | | | 4 | 23 | 5 | 27 | 5 | 29 | 6.3 | 33 |
| 22 | 220 | | 4 | 28 | 5 | 33 | 5 | 37 | 6.3 | 42 | 6.3 | 46 | | | |
| 33 | 330 | 4 | 28 | 5 | 37 | 5 | 41 | 6.3 | 49 | 6.3 | 52 | | | | |
| 47 | 470 | 4 | 33 | 5 | 45 | 6.3 | 52 | 6.3 | 58 | | | | | | |
| 100 | 101 | 5 | 56 | 6.3 | 70 | | | | | | | | | | |
| 220 | 221 | 6.3 | 96 | | | | | | | | | | | | |

Rated ripple current (mA Arms) at 85°C 120Hz

Frequency coefficient of rated ripple current

| Frequency | 50 Hz | 120 Hz | 300 Hz | 1 kHz | 10 kHz or more |
|-------------|-------|--------|--------|-------|----------------|
| Coefficient | 0.70 | 1.00 | 1.17 | 1.36 | 1.50 |

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please select UUR(p.168), UUG(p.174) if high C/V products are required.
- Please refer to page 3 for the minimum order quantity.