

## Universal Reversible USB 2.0 Cable (Up / Down Angle Reversible A to Micro-B M/M), 6-ft.

MODEL NUMBER: **UR050-006-UDA**



### Highlights

- Next Generation USB Digital Device Connector
- Provides both Data and Power transfers
- USB 2.0 480Mbps Transfer rates
- Up / Down Angle Reversible "A" Male to Micro-B Male

### System Requirements

- Digital devices that use the USB Micro-B Female socket

### Package Includes

- 6-ft. USB 2.0 Up / Down Angle Reversible A to Micro-USB B Device Cable (A Male to Micro-B Male)

### Description

Tripp Lite UR050-006-UDA, 6-ft. USB 2.0 Up / Down Angle Reversible A to Micro-B cable takes the guesswork out of which way to position the "A" connector for plugging. Micro-USB is the next generation of USB connector that will be found on Cell Phones, PDA's, USB On-the-Go ( OTG) devices, Digital Cameras, and more. Smaller and more durable ( 10,000 insertion cycles) than the existing Mini-B connectors, the Micro-USB will also handle Power transfers, as well as Data. (For higher powered mobile devices such as tablets, use Tripp Lite's UR050-XXX-24G cables, such as the [UR050-003-24G](#) and [UR050-006-24G](#)) The USB Implementers Forum ( USB-IF) has designed the Micro-USB to eliminate many of the proprietary Mini connectors found on different manufacturers digital devices, and it will be the standard USB connection on phones from the major cell phone manufacturers. USB 2.0 rated cable handles 480Mbps data transfer rates.

### Features

- USB Up / Down Angle Reversible A Male to Micro-B Male, 6-ft.
- 480Mbps USB 2.0 Data Transfer Rates
- Data and Power transference

## Specifications

| INPUT              |       |
|--------------------|-------|
| Cable Length (ft.) | 6     |
| Cable Length (m)   | 1.8   |
| PHYSICAL           |       |
| Color              | Black |
| ENVIRONMENTAL      |       |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                     |                           |
|-------------------------------------|---------------------------|
| Operating Temperature Range         | -10/+75° C (14 to 167° F) |
| Storage Temperature Range           | -20/+80° C (-4 to 176° F) |
| <b>CONNECTIONS</b>                  |                           |
| Side A - Connector 1                | REVERSIBLE USB A (MALE)   |
| Side B - Connector 1                | MICRO-USB B (MALE)        |
| <b>WARRANTY</b>                     |                           |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>