


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF20292-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	1820 @ 0°C	810	5	38,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION				
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP				
A	DIMENSION CHANGES RELEASED	12/19/02 2/28/02	DRAWN BY L. WENGSTROM	APPV'D BY DATE F.D. 12/19/02	SIZE A	FSCM NO. 55335	DRAWING NO. BF20292-24B		
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 2/28/02	REVISION DATE 12/19/02	REV. NO. A	SHEET 1 OF 1