

Page
1 / 2

OPTIONS: / TTL DRIVE

```

FREQUENCY RANGE      : 0 - 3 GHz
IMPEDANCE            : 50 Ohms

```

FREQUENCY (GHz)	0 - 1	1 - 2	2 - 3
V.S.W.R ≤	1.15	1.20	1.25
INSERT. LOSS ≤	0.15 dB	0.20 dB	0.25 dB
ISOLATION ≥	85 dB	80 dB	75 dB
AVER. POWER (*)	400 W	300 W	240 W

ACTUATOR	: LATCHING
NOMINAL CURRENT AT 25°C (±10%)	: 320 mA
ACTUATOR VOLTAGE (Vcc)	: 12V (10.2 to 13V) /NEGATIVE COMMON
TERMINALS	: male D-sub 9 pins (4-40 UNC nuts)
TTL INPUTS (E) - High level	: 2.2 to 5.5V / 800µA at 5V
- Low level	: 0 to 0.8V / 20µA at 0.8V

CONNECTORS	: BNC fem. per MIL C 39012
LIFE	: 1.000.000 cycles
SWITCHING TIME (nominal voltage;25° C)	: < 15 ms
CONSTRUCTION	: splashproof
WEIGHT	: <185 g

OPERATING TEMPERATURE RANGE (°C) : -40 , +85
STORAGE TEMPERATURE RANGE (°C) : -55 , +85

(* : average power at 25° C)

