# 9001SKT35R31



| Main               |                              |  |
|--------------------|------------------------------|--|
| Lens type          | Fresnel plastic              |  |
| Light block supply | Full voltage<br>Full voltage |  |

#### Complementary

| Bezel material               | Plastic         |  |
|------------------------------|-----------------|--|
| Mounting diameter            | 1.18 in (30 mm) |  |
| Shape of signaling unit head | Round           |  |
| Operating mode               | Push-to-test    |  |

### Environment

| protective treatment    | TC   |
|-------------------------|------|
| IP degree of protection | IP66 |

## **Offer Sustainability**

| 785901959977   | 785901959977   |  |
|--|--|--|
| Compliant - since 0921 - Schneider Electric declaration of conformity  | Compliant - since 0921 - Schneider Electric declaration of conformity            |  |
| Reference not containing SVHC above the threshold  | Reference not containing SVHC above the threshold                                |  |
| WARNING: This product can expose you to chemicals including:   | WARNING: This product can expose you to chemicals including:                     |  |
| Nickel compounds, which is known to the State of California to cause cancer, and   | Nickel compounds, which is known to the State of California to cause cancer, and |  |
| Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. harm. |  |  |
| For more information go to www.p65warnings.ca.gov  | For more information go to www.p65warnings.ca.gov                                |  |
|  |  |  |

#### Contractual warranty

Warranty period

18 months

