

ROHS COMPLIANT

PRODUCT DATA DRAWING

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	NRN 42973	03/19	GPF

OAL (SEE TABLE)

MATERIAL:

CONNECTORS:

CABLE:

SHRINK TUBING:

PERFORMANCE:

IMPEDANCE:

FREQ. RANGE:

SEE NOTES

SEE NOTES

N/A

PROPRIETARY

50 OHMS

DC TO 40.0 GHz

2.4MM PLUG ( SF1611-60003)

SMPM R/A JACK (3222-40005)

T-FLEX 405

M23053/5

SV P/N	OAL
7016-0066	6.000
7016-0067	12.000

MATERIAL:	SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES:	UNLESS OTHERWISE SPECIFIED 1) ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES .005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63. MIL-STD-10. 6) DIA.'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN .005 T.I.R. 7) REMOVE ALL BURRS	Amphenol <b>SV MICROWAVE</b> 2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409		
FINISH:	SEE NOTES	FRACTIONAL: ±1/64    ANGULAR: X° ±1°0'    X°X' ±15'				
SURFACE AREA:	N/A	DECIMAL: .X ±.030 .XX ±.010 .XXX ±.005				
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.		INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994	TITLE: 2.4mm PLUG TO SMPM R/A JACK FOR Ø.085 T-FLEX 405 CABLE ASSEMBLY			
		THIRD ANGLE PROJECTION	DRAWN: SJ 03/29/19	SIZE B	CAGE CODE 95077	DWG. NO. 7016-0066-0067
			CHECKED: GPF 03/29/19	SCALE: 2:1		
APPROVED: GPF 03/29/19			SHEET 1 OF 1			