

## Fuse Blocks, 5 x 20 and 5 x 25 mm


Altech fuse terminals are also available with light indication - CF4U(L). A specially designed built-in circuit gives light indication in the event of fuse blow out. Thus, fault in a circuit can be easily located. No polarity is required.

### Important:

The disconnecting device is not suitable for interrupting load. The supply must be switched off before operating the slide link/lever.

† Fuses are sold separately see pages 100-101.

\* Add required voltage to part number as a suffix. i.e. CF4U(L)/6-60 V AC/DC.



|                                        |                                |
|----------------------------------------|--------------------------------|
| Terminal Width                         | 8 mm                           |
| Height x Length                        | 57.6 x 57 mm                   |
| Stripping Length                       | 9.5 mm                         |
| Insulation Material                    | Polyamide 6.6                  |
| Type of Connection                     | 2 screw clamps                 |
| LED Voltage                            | 6-60 V AC/DC<br>90-240 V AC/DC |
| Size of Fuse Used<br>Type of Fuse Used | Ø5x20, Ø5x25 mm<br>Glass       |
| Approvals                              |                                |
| Wire Range                             | 22-10 AWG                      |
| Voltage Rating                         | 600 V                          |
| Current Rating                         | 10 A                           |
| Torque                                 | 7 lb-in                        |
| Other Approvals                        |                                |

### Terminal Block

DIN Rail  
for ordering information  
refer to pages 90-91

End Stop  
for ordering information  
refer to page 92

|                 |         |  |
|-----------------|---------|--|
| Internal Jumper | 2 pole  |  |
|                 | 3 pole  |  |
|                 | 4 pole  |  |
|                 | 10 pole |  |

|                           |         |  |
|---------------------------|---------|--|
| Insulated Internal Jumper | 2 pole  |  |
|                           | 3 pole  |  |
|                           | 4 pole  |  |
|                           | 10 pole |  |

|             |         |  |
|-------------|---------|--|
| Current Bar | 2 pole  |  |
|             | 3 pole  |  |
|             | 4 pole  |  |
|             | 10 pole |  |

Shorting Sleeve & Screw

|                 |         |  |
|-----------------|---------|--|
| External Jumper | 2 pole  |  |
|                 | 3 pole  |  |
|                 | 4 pole  |  |
|                 | 10 pole |  |

Marking Tags (on terminal)  
(on Lever)

### CF4U†

**NEW**

No End Plate Required.

|                          |
|--------------------------|
| 8 mm                     |
| 57.6 x 57 mm             |
| 9.5 mm                   |
| Polyamide 6.6            |
| 2 screw clamps           |
| Ø5x20, Ø5x25 mm<br>Glass |
| 22-10 AWG                |
| 600 V                    |
| 10 A                     |
| 7 lb-in                  |

RoHS  
CE

| Cat. No. | Std. Pk. |
|----------|----------|
|----------|----------|

|      |     |
|------|-----|
| CF4U | 100 |
|------|-----|

|      |      |
|------|------|
| 32mm | 35mm |
|------|------|

|       |    |
|-------|----|
| CA702 | 50 |
| CA802 | 50 |

|          |     |
|----------|-----|
| CA711/2  | 100 |
| CA711/3  | 50  |
| CA711/4  | 50  |
| CA711/10 | 20  |

|     |     |
|-----|-----|
| MT8 | 100 |
| MT8 | 100 |

### CF4U(L)†\*

**NEW**

No Polarity Required.

|                                  |
|----------------------------------|
| 8 mm                             |
| 57.6 x 57 mm                     |
| 9.5 mm                           |
| Polyamide 6.6                    |
| 2 screw clamps                   |
| CF4U(L)/6-60V<br>CF4U(L)/90-240V |
| Ø5x20, Ø5x25 mm<br>Glass         |
| 22-10 AWG                        |
| 600 V                            |
| 10 A                             |
| 7 lb-in                          |

RoHS  
CE



| Cat. No. | Std. Pk. |
|----------|----------|
|----------|----------|

|          |    |
|----------|----|
| CF4U(L)* | 50 |
|----------|----|

|      |      |
|------|------|
| 32mm | 35mm |
|------|------|

|       |    |
|-------|----|
| CA702 | 50 |
| CA802 | 50 |

### CF4U(L) Only



|          |     |
|----------|-----|
| CA711/2  | 100 |
| CA711/3  | 50  |
| CA711/4  | 50  |
| CA711/10 | 25  |

|     |     |
|-----|-----|
| MT8 | 100 |
| MT8 | 100 |

**COLOR BLOCKS**  
(other than standard grey)

When ordering please add color suffix to Cat. No.

Example for color Red: **Cat.No./R**

| Color  | Ordering Suffix |
|--------|-----------------|
| Red    | R               |
| Yellow | Y               |
| Blue   | BU              |
| Green  | G               |

Consult Altech for availability:

|            |    |
|------------|----|
| Orange     | O  |
| Beige      | BG |
| Dark Brown | DB |
| Black      | BL |
| White      | W  |