

RADIALl®

Microwave components

TECHNICAL DATA SHEET

R410103121

2 W

DC- 8 GHz


SMC

COAXIAL ATTENUATOR

issue
15.jul.93

Page
1 / 1

DRAWING



General tolerances: +/- 0.5 mm

R F CHARACTERISTICS

FREQUENCY RANGE : DC - 8 GHz
 IMPEDANCE : 50 Ohms
 ATTENUATION - NOMINAL : 3 dB

FREQUENCY	DC- 4 GHz	4 - 8 GHz
V.S.W.R	<= 1.15	<= 1.30
DEVIATION (dB)	+ 0.3 / - 0.3	+ 0.5 / - 0.5

TEMPERATURE SENSITIVITY : $4 \times 10^{-4} \frac{\text{dB}}{\text{dB} \times ^\circ\text{C}}$

PEAK POWER at 25°C (1µs,1%.) : 100 W

AVERAGE POWER at 25°C : 2 W


MECHANICAL CHARACTERISTICS

CONNECTORS : SMC male/female per MIL-C 39012
 WEIGHT : < 5 g

ENVIRONMENTAL CHARACTERISTICS

OPERATING TEMPERATURE RANGE (°C) : -55 , +125

STORAGE TEMPERATURE RANGE (°C) : -55 , +125



QUALITY
Dpt app. _____

CREATION

PEN : CAT

EP : -----

Nom : KL

Date:13.apr.90

15.jul.93

New issue

ISSUE

REVISIONS

NAME

RADIALl®

101. Philibert Hoffmann Phone:33.1.49353535
 - Z.I Ouest - Fax :33.1.48546363
 93116 ROSNY/BOIS Cedex-FRANCE Tlx RADIA 235220F