

KZN New!
Series

- Adoption of innovative high stability electrolyte
- High ripple current and long endurance
- Rated voltage range : 6.3 to 100V_{dc}, Capacitance range : 8.2 to 22,000μF
- Endurance with ripple current : 6,000 to 10,000 hours at 105°C
- Non solvent resistant type
- RoHS Compliant

KZN

↑ Higher ripple
KZM P139



◆ SPECIFICATIONS

Items	Characteristics						
Category Temperature Range	-40 to +105°C						
Rated Voltage Range	6.3 to 100V _{dc}						
Capacitance Tolerance	±20% (M) (at 20°C, 120Hz)						
Leakage Current	I=0.01CV or 3μA, whichever is greater. Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20°C after 2 minutes)						
Dissipation Factor (tanδ)	Rated voltage (V _{dc})	6.3V 10V 16V 25V 35V 50V 63V 80V 100V					
	tanδ (Max.)	0.22 0.19 0.16 0.14 0.12 0.10 0.09 0.09 0.08					
	When nominal capacitance exceeds 1,000μF, add 0.02 to the value above for each 1,000μF increase. (at 20°C, 120Hz)						
Low Temperature Characteristics	Z(-25°C)/Z(+20°C)	2 max.					
	Z(-40°C)/Z(+20°C)	3 max. (at 120Hz)					
Endurance	The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for the specified period of time at 105°C.						
	Time	Case size	φ 5 & φ 6.3	φ 8×11.5L	φ 10×12.5L	φ 8×15L, 20L	φ 10×16L, 20L, 25L φ 12.5 to φ 18
		6.3V _{dc}	6,000 hours	8,000 hours	9,000 hours	9,000 hours	10,000 hours
		10 to 50V _{dc}	7,000 hours	9,000 hours	9,000 hours	10,000 hours	10,000 hours
	63 to 100V _{dc}	6,000 hours	8,000 hours	9,000 hours	9,000 hours	9,000 hours	10,000 hours
	Capacitance change	≤ ±25% of the initial value (6.3, 10V _{dc} : ≤ ±30%)					
	D.F. (tanδ)	≤ 200% of the initial specified value					
Leakage current	≤ The initial specified value						
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 500 hours at 105°C without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to Item 4.1 of JIS C 5101-4.						
	Capacitance change	≤ ±25% of the initial value (6.3, 10V _{dc} : ≤ ±30%)					
	D.F. (tanδ)	≤ 200% of the initial specified value					
	Leakage current	≤ The initial specified value					

◆ DIMENSIONS [mm]

● Terminal Code : E



φ D	5	6.3	8	10	12.5	16	18
φ d	0.5	0.5	0.6	0.6	0.6	0.8	0.8
F	2.0	2.5	3.5	5.0	5.0	7.5	7.5
D'	φ D + 0.5max.						
L'	L + 1.5max.						

◆ PART NUMBERING SYSTEM



Please refer to "Product code guide (radial lead type)"

◆ STANDARD RATINGS

WV (Vdc)	Cap (μF)	Case size φD×L(mm)	Impedance (Ωmax/100kHz)		Rated ripple current (mA _{rms} /105°C, 100kHz)	Part No.	WV (Vdc)	Cap (μF)	Case size φD×L(mm)	Impedance (Ωmax/100kHz)		Rated ripple current (mA _{rms} /105°C, 100kHz)	Part No.						
			20°C	-10°C						20°C	-10°C								
			6.3	220						5×11	0.38			1.2	345	EKZN6R3E□□221ME11D	16	5,600	16×25
470	6.3×11	0.17		0.51	540	EKZN6R3E□□471MF11D	6,800	16×31.5	0.016	0.048	4,100	EKZN160E□□682MLN3S							
820	8×11.5	0.075		0.23	945	EKZN6R3E□□821MHB5D	6,800	18×25	0.016	0.048	3,880	EKZN160E□□682MM25S							
1,200	8×15	0.059		0.18	1,250	EKZN6R3E□□122MH15D	8,200	16×35.5	0.014	0.042	4,280	EKZN160E□□822MLP1S							
1,200	10×12.5	0.053		0.16	1,330	EKZN6R3E□□122MJC5S	8,200	18×31.5	0.014	0.042	4,190	EKZN160E□□822MMN3S							
1,500	8×20	0.041		0.13	1,500	EKZN6R3E□□152MJ20D	10,000	16×40	0.013	0.039	4,580	EKZN160E□□103ML40S							
1,800	10×16	0.038		0.12	1,760	EKZN6R3E□□182MJ16S	10,000	18×35.5	0.012	0.036	4,380	EKZN160E□□103MMP1S							
2,700	10×20	0.028		0.084	1,960	EKZN6R3E□□272MJ20S	12,000	18×40	0.011	0.033	4,960	EKZN160E□□123MM40S							
2,700	12.5×16	0.035		0.11	1,900	EKZN6R3E□□272MK16S	25	68	5×11	0.38	1.2	450	EKZN250E□□680ME11D						
3,300	10×25	0.026		0.072	2,250	EKZN6R3E□□332MJ25S		150	6.3×11	0.17	0.51	700	EKZN250E□□151MF11D						
3,900	12.5×20	0.025		0.075	2,480	EKZN6R3E□□392MK20S		270	8×11.5	0.075	0.23	1,200	EKZN250E□□271MHB5D						
5,600	12.5×25	0.019		0.057	2,900	EKZN6R3E□□562MK25S		470	8×15	0.059	0.18	1,600	EKZN250E□□471MH15D						
6,800	12.5×30	0.018		0.054	3,450	EKZN6R3E□□682MK30S		470	10×12.5	0.053	0.16	1,700	EKZN250E□□471MJC5S						
6,800	16×20	0.021		0.063	3,250	EKZN6R3E□□682ML20S		560	8×20	0.041	0.13	1,960	EKZN250E□□561MH20D						
8,200	12.5×35	0.016		0.048	3,570	EKZN6R3E□□822MK35S		680	10×16	0.038	0.12	2,000	EKZN250E□□681MJ16S						
8,200	18×20	0.020		0.060	3,450	EKZN6R3E□□822MM20S		820	10×20	0.028	0.084	2,500	EKZN250E□□821MJ20S						
10,000	16×25	0.017		0.051	3,630	EKZN6R3E□□103ML25S		1,000	12.5×16	0.035	0.11	2,400	EKZN250E□□102MK16S						
12,000	16×31.5	0.016		0.048	4,100	EKZN6R3E□□123MLN3S		1,200	10×25	0.026	0.072	2,900	EKZN250E□□122MJ25S						
12,000	18×25	0.016		0.048	3,880	EKZN6R3E□□123MM25S		1,500	12.5×20	0.025	0.075	2,600	EKZN250E□□122MK20S						
15,000	16×35.5	0.014		0.042	4,280	EKZN6R3E□□153MLP1S		1,800	12.5×25	0.019	0.057	3,200	EKZN250E□□182MK25S						
15,000	18×31.5	0.014		0.042	4,190	EKZN6R3E□□153MMN3S		2,200	12.5×30	0.018	0.054	3,660	EKZN250E□□222MK30S						
18,000	16×40	0.013		0.039	4,580	EKZN6R3E□□183ML40S		2,200	16×20	0.021	0.063	3,330	EKZN250E□□222ML20S						
18,000	18×35.5	0.012		0.036	4,380	EKZN6R3E□□183MMP1S		2,700	12.5×35	0.016	0.048	4,120	EKZN250E□□272MK35S						
22,000	18×40	0.011		0.033	4,960	EKZN6R3E□□223MM40S		3,300	16×25	0.017	0.051	3,810	EKZN250E□□332ML25S						
100								3,300	18×20	0.020	0.060	3,450	EKZN250E□□332MM20S						
								4,700	16×31.5	0.016	0.048	4,100	EKZN250E□□472MLN3S						
								4,700	18×25	0.016	0.048	3,880	EKZN250E□□472MM25S						
								5,600	16×35.5	0.014	0.042	4,280	EKZN250E□□562MLP1S						
								5,600	18×31.5	0.014	0.042	4,190	EKZN250E□□562MMN3S						
								6,800	16×40	0.013	0.039	4,580	EKZN250E□□682ML40S						
								6,800	18×35.5	0.012	0.036	4,380	EKZN250E□□682MMP1S						
								8,200	18×40	0.011	0.033	4,960	EKZN250E□□822MM40S						
								16							47	5×11	0.38	1.2	450
							100								6.3×11	0.17	0.51	700	EKZN350E□□101MF11D
							180								8×11.5	0.075	0.23	1,200	EKZN350E□□181MHB5D
							220								8×15	0.059	0.18	1,600	EKZN350E□□221MH15D
							270								10×12.5	0.053	0.16	1,700	EKZN350E□□271MJC5S
							330								8×20	0.041	0.13	1,960	EKZN350E□□331MH20D
							390								10×16	0.038	0.12	2,000	EKZN350E□□391MJ16S
							470								10×20	0.028	0.084	2,500	EKZN350E□□471MJ20S
							560								12.5×16	0.035	0.11	2,400	EKZN350E□□561MK16S
							680								10×25	0.026	0.072	2,900	EKZN350E□□681MJ25S
							820								12.5×20	0.025	0.075	2,600	EKZN350E□□821MK20S
							1,200								12.5×25	0.019	0.057	3,200	EKZN350E□□122MK25S
							1,500								12.5×30	0.018	0.054	3,660	EKZN350E□□152MK30S
							1,500								16×20	0.021	0.063	3,330	EKZN350E□□152ML20S
							1,800								12.5×35	0.016	0.048	4,120	EKZN350E□□182MK35S
							1,800								16×25	0.017	0.051	3,810	EKZN350E□□182ML25S
							1,800								18×20	0.020	0.060	3,450	EKZN350E□□182MM20S
2,700	16×31.5	0.016	0.048	4,100	EKZN350E□□272MLN3S														
2,700	18×25	0.016	0.048	3,880	EKZN350E□□272MM25S														
3,300	16×35.5	0.014	0.042	4,280	EKZN350E□□332MLP1S														
3,300	18×31.5	0.014	0.042	4,190	EKZN350E□□332MMN3S														
3,900	16×40	0.013	0.039	4,580	EKZN350E□□392ML40S														
3,900	18×35.5	0.012	0.036	4,380	EKZN350E□□392MMP1S														
4,700	18×40	0.011	0.033	4,960	EKZN350E□□472MM40S														
50							27								5×11	0.40	1.3	450	EKZN500E□□270ME11D
							56	6.3×11	0.18	0.54	700	EKZN500E□□560MF11D							
							100	8×11.5	0.085	0.26	1,200	EKZN500E□□101MHB5D							
							120	8×15	0.065	0.20	1,600	EKZN500E□□121MH15D							
							150	10×12.5	0.073	0.22	1,280	EKZN500E□□151MJC5S							
							180	8×20	0.049	0.16	1,960	EKZN500E□□181MH20D							
							220	10×16	0.053	0.16	1,650	EKZN500E□□221MJ16S							
							330	10×20	0.038	0.12	2,060	EKZN500E□□331MJ20S							

□□ : Enter the appropriate lead forming or taping code.

◆STANDARD RATINGS

WV (Vdc)	Cap (μF)	Case size φD×L(mm)	Impedance (Ωmax/100kHz)		Rated ripple current (mA _{rms} / 105°C, 100kHz)	Part No.	WV (Vdc)	Cap (μF)	Case size φD×L(mm)	Impedance (Ωmax/100kHz)		Rated ripple current (mA _{rms} / 105°C, 100kHz)	Part No.
			20°C	-10°C						20°C	-10°C		
50	330	12.5×16	0.045	0.14	2,160	EKZN500E□□331MK16S	80	82	8×20	0.12	0.54	1,040	EKZN800E□□820MH20D
	390	10×25	0.032	0.10	2,420	EKZN500E□□391MJ25S		82	10×12.5	0.14	0.56	780	EKZN800E□□820MJC5S
	470	12.5×20	0.032	0.10	2,300	EKZN500E□□471MK20S		120	10×16	0.090	0.36	1,040	EKZN800E□□121MJ16S
	680	12.5×25	0.025	0.080	2,800	EKZN500E□□681MK25S		180	10×20	0.068	0.28	1,430	EKZN800E□□181MJ20S
	820	12.5×30	0.023	0.074	3,370	EKZN500E□□821MK30S		180	12.5×16	0.090	0.27	1,430	EKZN800E□□181MK16S
	820	16×20	0.026	0.084	3,070	EKZN500E□□821ML20S		220	10×25	0.055	0.22	1,620	EKZN800E□□821ML25S
	1,000	12.5×35	0.021	0.067	3,810	EKZN500E□□102MK35S		270	12.5×20	0.048	0.15	1,750	EKZN800E□□271MK20S
	1,200	16×25	0.022	0.070	3,510	EKZN500E□□122ML25S		390	12.5×25	0.038	0.12	2,210	EKZN800E□□391MK25S
	1,200	18×20	0.025	0.075	3,120	EKZN500E□□122MM20S		470	12.5×30	0.033	0.11	2,400	EKZN800E□□471MK30S
	1,500	16×31.5	0.019	0.057	4,030	EKZN500E□□152MLN3S		470	16×20	0.036	0.12	1,950	EKZN800E□□471ML20S
	1,500	18×25	0.021	0.063	3,530	EKZN500E□□152MM25S		560	12.5×35	0.026	0.078	2,600	EKZN800E□□561MK35S
	1,800	16×35.5	0.016	0.048	4,220	EKZN500E□□182MLP1S		680	16×25	0.028	0.084	2,430	EKZN800E□□681ML25S
	2,200	16×40	0.014	0.042	4,500	EKZN500E□□222ML40S		680	18×20	0.032	0.096	2,270	EKZN800E□□681MM20S
	2,200	18×31.5	0.016	0.048	4,080	EKZN500E□□222MMN3S		820	16×31.5	0.022	0.066	2,640	EKZN800E□□821MLN3S
	2,700	18×35.5	0.013	0.039	4,270	EKZN500E□□272MMP1S		820	18×25	0.027	0.081	2,500	EKZN800E□□821MM25S
	3,300	18×40	0.012	0.036	4,850	EKZN500E□□332MM40S		1,000	16×35.5	0.020	0.060	2,860	EKZN800E□□102MLP1S
63	18	5×11	0.52	2.3	240	EKZN630E□□180ME11D	1,200	16×40	0.018	0.054	3,510	EKZN800E□□122ML40S	
	39	6.3×11	0.24	1.1	420	EKZN630E□□390MF11D	1,200	18×31.5	0.020	0.060	2,860	EKZN800E□□122MMN3S	
	68	8×11.5	0.15	0.68	720	EKZN630E□□680MHB5D	1,500	18×35.5	0.018	0.054	3,510	EKZN800E□□152MMP1S	
	100	8×15	0.10	0.45	990	EKZN630E□□101MH15D	1,800	18×40	0.017	0.051	3,860	EKZN800E□□182MM40S	
	120	8×20	0.077	0.35	1,200	EKZN630E□□121MH20D	100	8.2	5×11	0.72	3.2	220	EKZN101E□□8R2ME11D
	120	10×12.5	0.090	0.36	990	EKZN630E□□121MJC5S		18	6.3×11	0.34	1.5	370	EKZN101E□□180MF11D
	180	10×16	0.061	0.25	1,200	EKZN630E□□181MJ16S		33	8×11.5	0.20	0.90	620	EKZN101E□□330MHB5D
	270	10×20	0.045	0.18	1,570	EKZN630E□□271MJ20S		47	8×15	0.14	0.63	780	EKZN101E□□470MH15D
	270	12.5×16	0.058	0.18	1,570	EKZN630E□□271MK16S		56	8×20	0.12	0.54	1,040	EKZN101E□□560MH20D
	330	10×25	0.037	0.12	1,990	EKZN630E□□331MJ25S		56	10×12.5	0.14	0.56	780	EKZN101E□□560MJC5S
	390	12.5×20	0.033	0.10	1,990	EKZN630E□□391MK20S		82	10×16	0.090	0.36	1,040	EKZN101E□□820MJ16S
	560	12.5×25	0.026	0.080	2,460	EKZN630E□□561MK25S		100	10×20	0.068	0.28	1,430	EKZN101E□□101MJ20S
	680	12.5×30	0.024	0.075	2,760	EKZN630E□□681MK30S		120	12.5×16	0.090	0.27	1,430	EKZN101E□□121MK16S
	680	16×20	0.027	0.085	2,380	EKZN630E□□681ML20S		150	10×25	0.055	0.22	1,620	EKZN101E□□151MJ25S
	820	12.5×35	0.022	0.068	3,040	EKZN630E□□821MK35S		180	12.5×20	0.048	0.15	1,750	EKZN101E□□181MK20S
	820	18×20	0.026	0.078	2,530	EKZN630E□□821MM20S		220	12.5×25	0.038	0.12	2,210	EKZN101E□□221MK25S
1,000	16×25	0.024	0.072	2,890	EKZN630E□□102ML25S	270		12.5×30	0.033	0.11	2,400	EKZN101E□□271MK30S	
1,200	16×31.5	0.020	0.060	3,280	EKZN630E□□122MLN3S	270		16×20	0.036	0.12	1,950	EKZN101E□□271ML20S	
1,200	18×25	0.022	0.066	2,930	EKZN630E□□122MM25S	390		12.5×35	0.026	0.078	2,600	EKZN101E□□391MK35S	
1,500	16×35.5	0.018	0.054	3,440	EKZN630E□□152MLP1S	390		16×25	0.028	0.084	2,430	EKZN101E□□391ML25S	
1,500	18×31.5	0.018	0.054	3,380	EKZN630E□□152MMN3S	390	18×20	0.032	0.096	2,270	EKZN101E□□391MM20S		
1,800	16×40	0.016	0.048	3,690	EKZN630E□□182ML40S	470	16×31.5	0.022	0.066	2,640	EKZN101E□□471MLN3S		
1,800	18×35.5	0.017	0.051	3,550	EKZN630E□□182MMP1S	560	16×35.5	0.020	0.060	2,860	EKZN101E□□561MMP1S		
2,200	18×40	0.015	0.045	3,930	EKZN630E□□222MM40S	560	18×25	0.027	0.081	2,500	EKZN101E□□561MM25S		
80	12	5×11	0.72	3.2	220	EKZN800E□□120ME11D	680	16×40	0.018	0.054	3,510	EKZN101E□□681ML40S	
	27	6.3×11	0.34	1.5	370	EKZN800E□□270MF11D	680	18×31.5	0.020	0.060	2,860	EKZN101E□□681MMN3S	
	47	8×11.5	0.20	0.90	620	EKZN800E□□470MHB5D	820	18×35.5	0.018	0.054	3,510	EKZN101E□□821MMP1S	
	68	8×15	0.14	0.63	780	EKZN800E□□680MH15D	1,000	18×40	0.017	0.051	3,860	EKZN101E□□102MM40S	

□□ : Enter the appropriate lead forming or taping code.

◆RATED RIPPLE CURRENT MULTIPLIERS

●Frequency Multipliers

Capacitance (μF)	Frequency (Hz)			
	120	1k	10k	100k
8.2 to 180	0.40	0.75	0.90	1.00
220 to 560	0.50	0.85	0.94	1.00
680 to 1,800	0.60	0.87	0.95	1.00
2,200 to 3,900	0.75	0.90	0.95	1.00
4,700 to 22,000	0.85	0.95	0.98	1.00

Note : The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.