## Product datasheet Characteristics

## 9050JCK17V36





Main	
Range of product	9050JCK
Product or component type	Timer
Time delay type	On-delay
Time delay range	0.330 min
[Uc] control circuit voltage	12 V AC/DC

## Complementary

Hold-in power consumption in VA	2 VA	
Line Rated Current	10 A	
Switch function	DPDT	
Contacts type and composition	2 NO + 2 NC	
Contacts material	Silver nickel	
Maximum switching voltage	240 V AC	
Mounting support	Socket	
Pin number	8	
Shape of pin	Tubular	
Product compatibility	8501NR51 8501NR52	
Environment		
product certifications	CE RoHS UL listed UL recognized	
ambient air temperature for operation	-18150 °F	
height	2.4 in (61 mm)	
width	1.69 in (43 mm)	

## **Offer Sustainability**

depth

Green Premium product	Green Premium product
Compliant - since 0627 - Schneider Electric declaration of conformity	Compliant - since 0627 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Nickel compounds, which is known to the State of California to cause cancer, and	Nickel compounds, which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Stat of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.

4.09 in (104 mm)

For more information go to www.p65warnings.ca.gov



For more information go to www.p65warnings.ca.gov

Warranty period

