# 9001SK43J1



#### Main

Bezel material	Black plastic
Device short name	К
Enclosure type	Weatherproof enclosure dust and oil resistant indoor/outdoor
Mounting diameter	1.18 in (30 mm)

### Complementary

Cap/operator or lens colour	Without cap	
Contacts type and composition	Without contact block	
Light block supply	Via transformer 110 V AC 50/60 Hz Via transformer 120 V AC 50/60 Hz	
Operator position information	3 positions	
Operator profile	Without knob	
Operator profile	1 projecting push-button	
Type of operator	Maintained	

#### **Environment**

NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13	
product certifications	CE	
	UL listed file E42259 CCN NKCR	
	CSA LR24590 class 3211 03	

## Offer Sustainability

785901048428	785901048428
Compliant - since 0921 - Schneider Electric declaration of conformity	Compliant - since 0921 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

#### Contractual warranty

Warranty period	18 months