

PRODUCT DATASHEET F15384_JENNY-8X1-T4-G2

JENNY-8X1-T4-G2

IESNA Type IV light distribution for wider roads and large outdoor areas

TECHNICAL SPECIFICATIONS:

Dimensions 280.1 x 35.1 mm

Height 17 mm

Fastening

ROHS compliant yes 10

MATERIAL SPECIFICATIONS:

ComponentTypeMaterialColourFinishJENNY-8X1-T4-G2Multi-lensSiliconeclear

ORDERING INFORMATION:


Component Qty in box MOQ MPQ Box weight (kg)

F15384_JENNY-8X1-T4-G2 130 20 10 9.0 » Box size: 398 x 298 x 265 mm



PRODUCT DATASHEET

F15384_JENNY-8X1-T4-G2






PRODUCT DATASHEET F15384_JENNY-8X1-T4-G2

PHOTOMETRIC DATA (MEASURED):

CREE 💠

LED XHP70 **FWHM** Asymmetric Efficiency 93 % Peak intensity 0.5 cd/lm LEDs/each optic 1 Light colour White Required components:

C14436_JENNY-HLD-A-BLK





PRODUCT DATASHEET

F15384_JENNY-8X1-T4-G2

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

4/4

www.ledil.com/ where_to_buy