



Product: [29511](#)

VFD 300% Gnd, 3C+G #14 Str TC, XLPE Ins+PVC Gnd, OS+TC Brd, 1 Pr #16 Str TC XLPE IS, Blk PVC Jkt, 600V TC-ER 90C Dry/Wet 1000V Flexible Motor Supply Cable

[Request Sample](#)

Product Description

Belden 300% Ground Flexible VFD, 3 Conductor 14AWG (41x30) Tinned Copper, XLPE Insulation M4 Color Code+PVC Insulated Ground, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, 1 Pair 16AWG (26x30) Tinned Copper XLPE Beldfoil, Black PVC Outer Jacket, 600V TC-ER 90C Dry/Wet 1000V Flexible Motor Supply Cable 1000V CSA AWM I/II A/B 600V CIC TC SUN RES DIR BUR Oil Resistant

Technical Specifications

Product Overview

Suitable Applications:	AC Motor drives, VFD, Variable Frequency drives
------------------------	---

Physical Characteristics (Overall)

Conductor

Element	AWG	Stranding	Material	No. of Conductors
Conductor	14	41x30	TC - Tinned Copper	3
Brake Pair	16	26x30	TC - Tinned Copper	2
Ground	14	41x30	TC - Tinned Copper	1

Conductor Count:	5
------------------	---

Insulation

Material	Nominal Wall Thickness
XLP, XLPO, XLPE (Thermoset)	0.046 in
XLP, XLPO, XLPE (Thermoset)	0.032 in
PVC - Polyvinyl Chloride	0.047 in

Color Chart

Number	Color
1	Black #1
2	Black #2
3	Black #3
4	Black and White Pair
5	Green/Yellow

Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Tape	Alum / Poly	Beldfoil®	100 %	TC - Tinned Copper	18

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Alum / Poly / Alum	Duofoil®	100 %	TC - Tinned Copper	14	41x30
Braid	2	TC - Tinned Copper		85 %			

Outer Shield Table Note:	Duofoil+Braid is over Power conductors only, Brake Pair has only the Foil Inner Shield
--------------------------	--

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
----------	------------------	------------------------	---------

PVC - Polyvinyl Chloride	0.82 in	0.075 in	Yes
--------------------------	---------	----------	-----

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Inner Shield DCR
2.52 Ohm/1000ft	4.99 Ohm/1000ft
4 Ohm/1000ft	4.99 Ohm/1000ft
2.52 Ohm/1000ft	

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Shield
23 pF/ft	42 pF/ft
34 pF/ft	
23 pF/ft	42 pF/ft

Inductance

Nominal Inductance
0.213 µH/ft
0.213 µH/ft

Voltage

UL Voltage Rating
1000 V RMS
600 V RMS (Type TC)

Temperature Range

UL Temp Rating:	90°C Dry, 90°C Wet
Operating Temp Range:	-40°C To +90°C

Mechanical Characteristics

Max Recommended Pulling Tension:	368 lbs
Min Bend Radius/Minor Axis:	8.2 in

Standards

NEC Articles:	336 - ER
NEC/(UL) Specification:	RHW-2 Singles, TC-ER, XHHW-2
CEC/C(UL) Specification:	CIC, TC
CSA AWM Specification:	AWM I/II A/B
PMSHA Specification:	P-07-KA070003
Other Specification:	1000V UL Flexible Motor Supply Cable

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-09-21
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Burial:	Yes
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT4
IEEE Flammability:	1202, 383
UL voltage rating:	1000 V RMS (Flexible Motor Supply Cable)

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
29511 010100	Black	Reel	100 ft	612825137481
29511 010500	Black	Reel	500 ft	612825137504
29511 0101000	Black	Reel	1,000 ft	612825137498
29511 0105000	Black	Reel	5,000 ft	612825137511

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

History

Update and Revision:	Revision Number: 0.352 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.