

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1054440001](#)
Status: **Active**
Overview: [Consumer USB Products](#)
Description: Universal Serial Bus (USB) Shielded I/O Plug, Type C, Right Angle, Surface Mount, 0.76µm Gold (Au) Plating, Tray

Documents:
[3D Model](#)
[Drawing \(PDF\)](#)
[Product Specification 1054440001 \(PDF\)](#)
[Application Specification 1054440001 \(PDF\)](#)
[Packaging Specification 1054440001 \(PDF\)](#)
[RoHS Certificate of Compliance \(PDF\)](#)

General	
Product Family	I/O Connectors
Series	105444
Application	Wire-to-Board
Comments	Nickel underplating
Component Type	Plug
Overview	Consumer USB Products
Product Name	USB 3.1
Type	C
UPC	889056292740
Physical	
Circuits (Loaded)	22
Circuits (maximum)	22
Color - Resin	Black
Durability (mating cycles max)	10000
Gender	Plug
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	0.633/g
Number of Rows	2
Orientation	Right Angle
PCB Locator	Yes
PCB Retention	None
PCB Thickness - Recommended	0.80mm
Packaging Type	Tray
Panel Mount	Yes
Pitch - Mating Interface	0.50mm
Pitch - Termination Interface	0.50mm
Plating min - Mating	0.762µm
Plating min - Termination	3.048µm
Polarized to Mating Part	No
Polarized to PCB	Yes
Ports	1
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-30°C to +85°C
Termination Interface: Style	Surface Mount
Electrical	
Current - Maximum per Contact	0.25A, 1.25A, 5.0A
Grounding to Panel	None
Shield Type	Full Shield



Series image - Reference only

EU ELV
Not Relevant

EU RoHS Compliant REACH SVHC Not Contained Per -ED/79/2015 (17 December 2015) Halogen-Free Status Low-Halogen Need more information on product environmental compliance? Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.	China RoHS China ROHS ELV
	Green Image Not Relevant

Search Parts in this Series
[105444](#) Series

Mates With
USB Type C Receptacle

Shielded
Voltage - Maximum

Yes
30V AC (RMS)

Material Info

Reference - Drawing Numbers

Application Specification

1054440001

Packaging Specification

1054440001

Product Specification

1054440001

Sales Drawing

1054440001

This document was generated on 06/17/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION