




LOC		DIST		REVISIONS					
AD		00		REV	LYR	DESCRIPTION	DATE	OWN	APVD
				C1		REVISED PER ECO-12-003973	05JUN2012	KH	AS

- 1


HOUSING: LCP, UL94V-0, BLACK.
CONTACT: PHOSPHOR BRONZE.
POST: BRASS WIRE.
- 2

CONTACT: 0.76µm GOLD PER ASTM B 488 IN CONTACT AREA,
1.27µm MIN TIN-LEAD
ON PCB TAIL,
OVER 1.27µm MIN NICKEL PER
SAE AMS-QQ-N-290 OVER ALL.
POST: 1.27µm MIN NICKEL.
- 4

CONTACT: 0.76µm GOLD PER ASTM B 488 IN CONTACT AREA,
0.50µm MIN MATTE TIN PER ASTM B 545
ON PCB TAIL,
OVER 1.27µm MIN NICKEL PER
SAE AMS-QQ-N-290 OVER ALL.
POST: 1.27µm MIN NICKEL.
- 6

POWER PIN PAIRS INDICATED ARE COMMONED INSIDE ASSEMBLY.

FINISH	DESCRIPTION	PART NO
4	9 SINGLE END, NONSEQUENTIAL WAFERS AND 7 POWER WAFER	1410997-2
2	9 SINGLE END, NONSEQUENTIAL WAFERS AND 7 POWER WAFER	1410997-1

THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN B. CARBO 25JUL2006	 TE Connectivity	
DIMENSIONS:		CHK G. GRIFFITH 25JUL2006		
mm		APVD G. GRIFFITH 25JUL2006	NAME	
		PRODUCT SPEC 108-2072 APPLICATION SPEC	RIGHT ANGLE PLUG ASSEMBLY, LEFT END, FULL, 25.4mm, POWER COMBINATION, MULTIGIG RTI, DAUGHTERCARD CONNECTOR	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		114-13056	SIZE	
9 PLC ±0		WEIGHT -	CAGE CODE	
1 PLC ±0.13			DRAWING NO	
3 PLC ±0.013			RESTRICTED TO	
4 PLC ±0.013			A100779C=1410997	
ANGLES ±1°		CUSTOMER DRAWING		
FINISH		SCALE 8:1		
		SHEET 1 OF 1		
		REV C		