



- NOTE:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERMINAL NUMBERS FOR REF ONLY
 4. RATING: 5A @ 250VAC; 8A @125VAC; 4A@ 250VAC
 5. INSULATION RESISTANCE: 50 MEGA-OHMS (INITIAL)
 6. ELECTRICAL LIFE: 30,000 MAKE-AND-BREAK CYCLES
 7. CONTACT MATERIAL: SILVER
 8. OPERATING TEMP.: -25°C to 55°C
 9. STORAGE TEMP.: -40°C to 70°C
 10. ▲ DENOTES CRITICAL PARAMETER.
 11. 2002/95/EC (ROHS) COMPLIANT



TITLE SPDT ILLUMINATED CONTACT BLOCK

| | | | | |
|-----|--------|-------------------------|--------|----|
| A | 17617 | RELEASED FOR PRODUCTION | 9/4/07 | BF |
| REV | PCR NO | DESCRIPTION | DATE | BY |

| | | | | |
|-------|----------|----|---------|-----|
| SCALE | DATE | DR | DWG | REV |
| 2:1 | 9/4/2007 | BF | F080001 | A |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED