



## OeM4215-26.00M TCVCXO Oscillator

November 2010

- Pletronics' OeM4 is from the OeXO™ Series of temperature compensated voltage controlled crystal oscillator with a CMOS output.
- Tube packaging is available
- Hermetically sealed Metal Package to replace DIP/DIL OCXOs
- Supply Voltage range: 3.10 to 12.0V

**Pletronics Inc. certifies this device is in accordance with the  
RoHS 6/6 (2002/95/EC) and WEEE (2002/96/EC) directives.**

Pletronics Inc. guarantees the device does not contain the following:

Cadmium, Hexavalent Chromium, Lead, Mercury, PBB's, PBDE's

Weight of the Device: 4.00 grams

Moisture Sensitivity Level: 1 As defined in J-STD-020D.1

Second Level Interconnect code: e1



### Absolute Maximum Ratings:

| Parameter                      | Unit                              |
|--------------------------------|-----------------------------------|
| V <sub>CC</sub> Supply Voltage | -0.5V to +12.0V                   |
| V <sub>CONTROL</sub> Voltage   | -0.5V to +3.0V or limited to ±5mA |
| V <sub>O</sub> Output Voltage  | -0.5V to +6.0V                    |

### Thermal Characteristics


The maximum die or junction temperature is 155°C

The thermal resistance junction to board is 120°C/Watt depending on the solder pads, ground plane and construction of the PCB.

### ESD Rating

| Model                | Minimum Voltage | Conditions              |
|----------------------|-----------------|-------------------------|
| Human Body Model     | 1500            | MIL-STD-883 Method 3115 |
| Charged Device Model | 1000            | JESD 22-C101            |

### Part Marking:



PLE = Pletronics  
 OEM4 = Model number of the series  
 26.00 = frequency in MHZ  
 4215 = Model number  
 YMD = Year, Month and Date of manufacture  
 zz = internal factory code

### Codes for Date Code YMD

| Code | 0    | 1    | 2    | 3    | 4    | Code  | A   | B   | C   | D   | E   | F   | G   | H   | J   | K   | L   | M   |
|------|------|------|------|------|------|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Year | 2010 | 2011 | 2012 | 2013 | 2014 | Month | JAN | FEB | MAR | APR | MAY | JUN | JUL | AUG | SEP | OCT | NOV | DEC |

| Code | 1  | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | A  | B  | C  | D  | E  | F  | G  |
|------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| Day  | 1  | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | 10 | 11 | 12 | 13 | 14 | 15 | 16 |
| Code | H  | J  | K  | L  | M  | N  | P  | R  | T  | U  | V  | W  | X  | Y  | Z  |    |
| Day  | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 |    |

### Reliability: Environmental Compliance

| Parameter        | Condition                            |
|------------------|--------------------------------------|
| Mechanical Shock | MIL-STD-883 Method 2002, Condition B |
| Vibration        | MIL-STD-883 Method 2007, Condition A |
| Solderability    | MIL-STD-883 Method 2003              |
| Thermal Shock    | MIL-STD-883 Method 1011, Condition A |

### Package Labeling

Label is 1" x 2.6" (25.4mm x 66.7mm)



Font is Courier New

Bar code is 39-Full ASCII

The bar code will show the actual Part Number OEM4215-26.00M

Label is 1" x 2.6" (25.4mm x 66.7mm)

Font is Arial




### Electrical Specification over the specified temperature range.

| Item                                                                 | Min                        | TYP                                        | Max                        | Unit            | Condition                                                                                                                   |
|----------------------------------------------------------------------|----------------------------|--------------------------------------------|----------------------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------|
| Frequency Stability over temperature                                 | -250                       | -                                          | 250                        | ppb             | Over -40°C to 85°C<br>at fixed supply voltage + load (reference to midpoint min/max frequency)                              |
| Holdover                                                             | -250<br>-125               | 0<br>0                                     | 250<br>125                 | ppb<br>ppb      | Over -40°C to 85°C for 24 hours<br>Over $\pm 5^\circ\text{C}$ change for 24 hours                                           |
| Frequency Calibration                                                | -2.0                       | -                                          | 2.0                        | ppm             | Frequency offset at 25°C, 60 minutes after reflow.                                                                          |
| Supply voltage stability                                             | -10                        | 0                                          | 10                         | ppb             | $\pm 2\%$ variation in supply voltage                                                                                       |
| Load sensitivity                                                     | -5                         | -                                          | 5                          | ppb             | 10K ohm $\pm 10\%$    15 pF $\pm 10\%$                                                                                      |
| Warm Up                                                              | -                          | 0.4                                        | 3.0                        | S               | Time to reach specified frequency                                                                                           |
| Aging rate following reflow                                          | -<br>-<br>-                | $\pm 10$<br>$\pm 3$<br>$\pm 1$             | -<br>-<br>-                | ppb/day         | 1 day after reflow<br>7 days after reflow<br>30 days after reflow                                                           |
| Long term stability (Aging)                                          | -1000<br>-1500<br>-4600    | -<br>-<br>-                                | 1000<br>1500<br>4600       | ppb             | after 1 year<br>after 5 years<br>after 15 years                                                                             |
| Output Waveform                                                      | CMOS                       |                                            |                            |                 |                                                                                                                             |
| Output $V_{\text{HIGH}}$                                             | 2.80                       | -                                          | -                          | V               | Load: 10K ohm $\pm 10\%$    15 pF $\pm 10\%$<br>Vth: $T_R$ and $T_F$ 10% and 90% of amplitude<br>Vth: D.C. 50% of amplitude |
| Output $V_{\text{LOW}}$                                              | -                          | -                                          | 0.20                       | V               |                                                                                                                             |
| $T_{\text{RISE}}$ and $T_{\text{FALL}}$                              | -                          | -                                          | 4.0                        | nS              |                                                                                                                             |
| Duty Cycle                                                           | 40                         | 50                                         | 60                         | %               |                                                                                                                             |
| Phase Noise<br>1 Hz<br>10 Hz<br>100 Hz<br>1 KHz<br>10 KHz<br>100 KHz | -<br>-<br>-<br>-<br>-<br>- | -71<br>-92<br>-115<br>-135<br>-148<br>-149 | -<br>-<br>-<br>-<br>-<br>- | dBc/Hz          | at 25°C                                                                                                                     |
| Jitter                                                               | -                          | -                                          | 0.6                        | pS              | Frequency offset from carrier 12kHz to 20MHz                                                                                |
| V Supply Range <sup>1</sup> $V_{\text{CC}}$                          | 3.10                       | -                                          | 12.0                       | Volts           |                                                                                                                             |
| Supply Current $I_{\text{CC}}$                                       | -                          | -                                          | 6.0                        | mA              |                                                                                                                             |
| $V_{\text{CONTROL}}$ Range                                           | 0.5                        | -                                          | 2.50                       | Volts           | 1.50 volts nominal                                                                                                          |
| $V_{\text{CONTROL}}$ Input Current                                   | -50                        | -                                          | 50                         | uA              |                                                                                                                             |
| Frequency Pullability                                                | 5                          | -                                          | 10                         | $\pm\text{ppm}$ | Slope positive                                                                                                              |
| Linearity                                                            | -                          | 0.05                                       | 2.0                        | %               | In accordance with MIL-PRF-55310                                                                                            |
| Operating Temperature                                                | -40                        | -                                          | +85                        | °C              |                                                                                                                             |
| Storage Temperature                                                  | -55                        | -                                          | +95                        | °C              |                                                                                                                             |

Note: <sup>1</sup> For correct operation a 10nF supply de-coupling capacitor should be placed next to the device.

## Mechanical:



### Cover:

Kovar  
Electroless Nickel Plated  
1 μinch (25 μm) typical  
Resistance welded to base

### Base:

Kovar  
Glass to metal sealed leads

### Label:

Laser marked

Pin 7 Connected to case

<sup>1</sup> Nominal dimension

|                | Inches            | mm               |
|----------------|-------------------|------------------|
| A              | 0.787 $\pm$ 0.005 | 20.00 $\pm$ 0.13 |
| B              | 0.487 $\pm$ 0.005 | 12.37 $\pm$ 0.13 |
| C              | 0.225 $\pm$ 0.011 | 5.72 $\pm$ 0.28  |
| D <sup>1</sup> | 0.250             | 6.35             |
| E <sup>1</sup> | 0.020             | 0.51             |
| F <sup>1</sup> | 0.031             | 0.79             |
| G <sup>1</sup> | 0.094             | 2.37             |
| H <sup>1</sup> | 0.300             | 7.62             |
| I <sup>1</sup> | 0.600             | 15.24            |
| J <sup>1</sup> | 0.094             | 2.37             |

**Not to scale**

| Pin | Name                 | Function                                                                    |
|-----|----------------------|-----------------------------------------------------------------------------|
| 1   | V <sub>CONTROL</sub> | EFC, electronics frequency control. 1.5V is nominal input                   |
| 7   | Ground (case)        |                                                                             |
| 8   | Output               | CMOS output                                                                 |
| 14  | V <sub>CC</sub>      | Power supply. Be sure to bypass near the pin with 10nF low noise capacitor. |

## Layout and application information

For Optimum Stability and Jitter Performance, Pletronics recommends:

- a ground plane under the device
- no large transient signals (both current and voltage) should be routed under the device
- do not layout near a large magnetic field such as a high frequency switching power supply
- do not place near piezoelectric buzzers or mechanical fans.
- minimize air flow across the device

## PCB Mounting (typical for lead free processing)

**Hand soldering is recommended.**

Wave solder at 255°C to 280°C with maximum wave exposure of 15 seconds

Reflow solder maximum exposure of 245°C for 15 seconds

Soldering done in a nitrogen atmosphere enhances the solder joint quality.

**IMPORTANT NOTICE**

Pletronics Incorporated (PLE) reserves the right to make corrections, improvements, modifications and other changes to this product at anytime. PLE reserves the right to discontinue any product or service without notice. Customers are responsible for obtaining the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to PLE's terms and conditions of sale supplied at the time of order acknowledgment.

PLE warrants performance of this product to the specifications applicable at the time of sale in accordance with PLE's limited warranty. Testing and other quality control techniques are used to the extent PLE deems necessary to support this warranty. Except where mandated by specific contractual documents, testing of all parameters of each product is not necessarily performed.

PLE assumes no liability for application assistance or customer product design. Customers are responsible for their products and applications using PLE components. To minimize the risks associated with the customer products and applications, customers should provide adequate design and operating safeguards.

PLE products are not designed, intended, authorized or warranted to be suitable for use in life support applications, devices or systems or other critical applications that may involve potential risks of death, personal injury or severe property or environmental damage. Inclusion of PLE products in such applications is understood to be fully at the risk of the customer. Use of PLE products in such applications requires the written approval of an appropriate PLE officer. Questions concerning potential risk applications should be directed to PLE.

PLE does not warrant or represent that any license, either express or implied, is granted under any PLE patent right, copyright, artwork or other intellectual property right relating to any combination, machine or process which PLE product or services are used. Information published by PLE regarding third-party products or services does not constitute a license from PLE to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from PLE under the patents or other intellectual property of PLE.

Reproduction of information in PLE data sheets or web site is permissible only if the reproduction is without alteration and is accompanied by associated warranties, conditions, limitations and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. PLE is not responsible or liable for such altered documents.

Resale of PLE products or services with statements different from or beyond the parameters stated by PLE for that product or service voids all express and implied warranties for the associated PLE product or service and is an unfair or deceptive business practice. PLE is not responsible for any such statements.

**Contacting Pletronics Inc.**

Pletronics Inc.  
19013 36<sup>th</sup> Ave. West  
Lynnwood, WA 98036-5761 USA

Tel: 425-776-1880  
Fax: 425-776-2760  
E-mail: [ple-sales@pletronics.com](mailto:ple-sales@pletronics.com)  
URL: [www.pletronics.com](http://www.pletronics.com)

Copyright © 2010, Pletronics Inc.