# Product datasheet Characteristics

## 9007MS09G0112

Device application	Machine tools
	Earth moving equipment
	General transportation
Device short name	MS

### Complementary

Line Rated Current	100 mA	
Body material	Cast zinc	
Cable length	3 ft	
Contact form	Form C SPDT	
Contacts material	Silver alloy, gold flashed	
Contact operation	Snap action	
Mounting support	Shoulder	
Operating force	80 ozf	
Permissible voltage	<= 28 V DC	
Switch actuation	Vertical	
Type of cable	STJO AWG 18 yellow	
Connector type	Mini 4 pins	
Type of operator	Spring return push rod plunger adjustable	

#### **Environment**

		<u>2</u> ,
ambient air temperature for operation	-4221 °F	
IP degree of protection	IP67	
NEMA degree of protection	NEMA 1/2/4/6/6P/12/13	
product certifications	CE CSA UL listed	and the state of t
shock resistance	35 gn	
vibration resistance	10 gn 751200 Hz	

#### Offer Sustainability

Not Green Premium product	Not Green Premium product	
Will not be Compliant	Will not be Compliant	
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold	
Available	Available	
Need no specific recycling operations	Need no specific recycling operations	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive harm.  harm.		
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov	