







REV.	ECN NO.	DATE	SIGN	DESCRIPTION



Recommend PCB Layout

Pin Assignment
Front ViewRecommended
Panel Cut-Out

- Note:
- * $\varnothing$ Important Dimension.
 - * Waterproof Rate: IP67.
 - * Housing: Nylon+GF, Black.
 - * Male Pin: Copper Alloy, Gold Plated.
 - * Shield: Zinc Alloy, Nickel Plated.
 - * Screw Nut: Copper Alloy, Nickel Plated.
 - * O-Ring: EPDM, Black.
 - * For Panel Thickness Max 3.0mm.
 - * Nut Torque: 4~6 kgf.cm.

UNIT:mm		TITLE		ITEM NO		DRAWN BY		DATE	
		M8 4Pin Panel M Conn. M Pin		8A-04PMMP-SF7001		Mila		2014-01-06	
TOLERANCE		SCALE		DWG NO		CHECKED BY		DATE	
.X ±0.25		3:1		8A-04PMMP-SF7001		Jimmy		2014-01-06	
.XX ±0.1		SIZE		CUSTOMER		APPROVED BY		DATE	
.XXX ±0.05		A4		ALTW		Jerry		2014-01-06	
ANGLES ±1°		REV.		SHEET		OF		DATE	
		A		1		1		2014-01-06	
		WC-REV.		QC		Inspection item		DATE	
		A.3						2014-01-06	

Amphenol LTW
安費諾亮泰企業股份有限公司