



① HOUSING MATERIAL: LIQUID CRYSTAL POLYMER PER ASTM D5138 LCP000 G30A 32250,
COLOR: NATURAL.

② CONTACT MATERIAL: PHOSPHOR-BRONZE.

③ CONTACT FINISH:
UNDERPLATE (ENTIRE CONTACT) –
0.00127 MIN NICKEL PER SAE-AMS-QQ-N-290.
ON MATING SURFACES–
CONFORMS TO ALL TESTING SPECIFIED FOR TELCORDIA
UNCONTROLLED ENVIRONMENT
ON LEADS–
0.0006 MIN TIN PER ASTM B 545, OVER UNDERPLATE
LUBRICATION (MIN MATING SURFACES)
SURFACE CONDITIONER AFTER PLATING.

④ PART MARKING, LOCATED APPROXIMATELY AS SHOWN.

⑤ CONTACT FINISH:
UNDERPLATE (ENTIRE CONTACT) –
0.00127 MIN NICKEL PER SAE-AMS-QQ-N-290.
ON MATING SURFACES–
0.00076 MIN NICKEL OR COBALT HARDENED GOLD
PER ASTM B-488 OVER UNDERPLATE.
ON LEADS–
0.0006 MIN TIN PER ASTM B 545, OVER UNDERPLATE
LUBRICATION (MIN MATING SURFACES)
SURFACE CONDITIONER AFTER PLATING.

⑥ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

A4805 (3/11)