



All dimensions are in mm; tolerances acc. ISO 2768 m-H

Interface

According to MIL-STD-348A, Fig. 326

Documents

N/A

Material and plating

Connector parts

Center contact
Outer contact
Dielectric

Material

CuBe
CuBe
PTFE

Plating

AuroDur®, gold plated
AuroDur®, gold plated

**Adaptor
SMP jack - jack****19K109-K00L5****Electrical data**

| | |
|---------------------------|--|
| Impedance | 50 Ω |
| Frequency | DC to 26.5 GHz |
| Return loss | ≥ 30 dB, DC to 4 GHz ≥ 18 dB, 4 to 18 GHz |
| Insertion loss | $\leq 0.05 \times \sqrt{f(\text{GHz})}$ dB, DC to 18 GHz |
| Insulation resistance | ≥ 5 G Ω |
| Center contact resistance | ≤ 6.0 m Ω |
| Outer contact resistance | ≤ 2.0 m Ω |
| Test voltage | 500 V rms |
| Working voltage | 335 V rms |
| Contact Current | 1.2A DC max. |

Mechanical data

| | |
|----------------------------------|-------------|
| Mating cycles | |
| if mating part is smooth bore | ≥ 1000 |
| if mating part is limited detent | ≥ 500 |
| if mating part is full detent | ≥ 100 |
| Center contact captivation | ≥ 7 N |
| Engagement force | |
| - smooth bore | 9 N max. |
| - limited detent | 45 N max. |
| - full detent | 68 N max. |
| Disengagement force | |
| - smooth bore | 2.2 N min. |
| - limited detent | 9 N min. |
| - full detent | 22 N min. |

Environmental data

| | |
|---------------------|--------------------------------------|
| Temperature range | -65°C to +155°C |
| Thermal shock | MIL-STD-202, Method 107, Condition B |
| Vibration | MIL-STD-202, Method 204, Condition B |
| Shock | MIL-STD-202, Method 213, Condition A |
| Moisture resistance | MIL-STD-202, Method 106 |
| RoHS | compliant |

Tooling

N/A

Suitable cables

N/A

Weight

Weight 0.4 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
|--|----------|-------------------|----------|------|--|-----------|---------------|
| A. König | 27/09/07 | Sa. Krautenbacher | 12.03.14 | b00 | 14-0352 | T. Krojer | 12.03.14 |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de | | | | | Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de | | Page 2 / 2 |