


LOC	DIST	REVISIONS				
GP	00	P	LTR	DESCRIPTION	DATE	APVD
			1	DRAFT	30AUG2012	SY



NOTES:

1. MATERIALS:
HOUSING: HIGH TEMP. THERMOPLASTIC GLASS/MINERAL FILLED UL94V-0
TERMINAL: COPPER ALLOY
2. FINISH:
TIN OPTION-0.76um MIN GOLD AT CONTACT AREA AND
1.27um MIN NICKEL UNDERPLATED OVER ALL
2.54um TIN AT SOLDER TAIL AREA
TIN-LEAD OPTION-0.76um MIN GOLD AT CONTACT AREA AND
1.27um MIN NICKEL UNDERPLATED OVER ALL
2.54um TIN-LEAD AT SOLDER TAIL AREA
3. REFER TO TE'S PRODUCT SPECIFICATION: 108-2473
FOR PLATED THROUGH-HOLE SPECIFICATION AND TORQUE FORCE
4. CONNECTOR WERE PACKED BY TRAY
REFER TO TE'S PACKAGING SPECIFICATION: 107-***
5. MATED WITH *-2169862-*
6. LASER MARK PART NUMBER AND DATE CODE (YYWWDS)
CAN BE AT THE OPPOSITE SIDE
7. KEEP OUT ZONE FROM OTHER COMPONENT

TRAY	N	6.90	6.90	5.70	2169872-8
		5.70	5.70	6.90	2169872-7
		6.90	5.70	5.70	2169872-6
		6.90	6.90	6.90	2169872-5
		6.90	6.90	5.70	2169872-4
		5.70	5.70	6.90	2169872-3
		6.90	5.70	5.70	2169872-2
		6.90	6.90	6.90	2169872-1
PACKAGING	PLATING TYP	P3	P2	P1	PART NUMBER

THIS PRINT IS
PRELIMINARY
UNQUALIFIED PRODUCT
CONTACT PRODUCT ENGINEERING
BEFORE USING THIS PRINT

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	30AUG2012		TE Connectivity PRELIMINARY IMPACT POWER 6 PAIR RIGHT ANGLE HEADER PRESS-FIT														
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC±-- 1 PLC±-- 2 PLC±0.25 3 PLC±-- 4 PLC±-- ANGLES±3°	CHK	30AUG2012						NAME										
		S. YAN																	
		APVD	30AUG2012																
		A. CAI																	
		PRODUCT SPEC																	
		108-2473																	
		APPLICATION SPEC																	
		114-32028																	
		WEIGHT		SIZE		CAGE CODE		DRAWING NO		RESTRICTED TO									
MATERIAL		FINISH		A3		00779		C-2169872		-									
				Customer Drawing								SCALE	1:1	SHEET	1	OF	3	REV	1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

TE CONNECTIVITY

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

GP

00

P

LTR

DESCRIPTION

DATE

DWN

APVD



-

SEE SHEET 1




-

-

-



MATED SYSTEM WITH 2169872



THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 30AUG2012

L. WANG

CHK 30AUG2012

S. YAN

APVD 30AUG2012

A. CAI

PRODUCT SPEC

108-2473

APPLICATION SPEC

114-32028

WEIGHT

-

Customer Drawing



TE Connectivity

NAME

IMPACT POWER 6 PAIR
RIGHT ANGLE HEADER
PRESS-FIT

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A300779

C-2169872


-

SCALE 1:1


SHEET 2 OF 3

REV 1


LOC	DIST	REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN	APVD	
	-	SEE SHEET 1	-	-	-	



CONNECTOR WITH PCB



RECOMMENDED PCB LAYOUT
(COMPONENT SIDE SHOWN)
MINIMUM BOARD THICKNESS: 1.60MM

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L. WANG 30AUG2012		 TE Connectivity							
		CHK S. YAN 30AUG2012									
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD A. CAT 30AUG2012		NAME					
		0 PLC ±--		IMPACT POWER 6 PAIR RIGHT ANGLE HEADER PRESS-FIT							
		1 PLC ±--									
		2 PLC ±0.25									
		3 PLC ±--									
		4 PLC ±--									
		ANGLES ±3°		SIZE		CAGE CODE		DRAWING NO		RESTRICTED TO	
MATERIAL		FINISH		PRODUCT SPEC 108-2473		A300779		C-2169872		-	
				APPLICATION SPEC 114-32028							
				WEIGHT -							
Customer Drawing						SCALE 1:1		SHEET 3 OF 3		REV 1	