

### Main

|                    |                                 |
|--------------------|---------------------------------|
| Device short name  | C                               |
| Enclosure type     | Standard                        |
| Head type          | Type C turret head rotary lever |
| Provided equipment | Receptacle                      |
| Series name        | Heavy duty                      |

### Complementary

|                            |                                   |
|----------------------------|-----------------------------------|
| Line Rated Current         | 10 A                              |
| Body material              | Zinc alloy                        |
| Contacts material          | Silver alloy (Ag/Ni)              |
| Contact operation          | Snap action                       |
| Material                   | Viton fluorocarbon sealing gasket |
| Maximum displacement angle | 90 °                              |
| Pilot light                | Without pilot lamp                |
| Specificity of operator    | Standard pre-travel               |
| Switch actuation           | CW and CCW                        |
| Tilting angle              | 10 °                              |
| Torque value               | 4 lbf.in                          |
| Tripping angle             | 4 °                               |

### Environment

|                                       |                        |
|---------------------------------------|------------------------|
| ambient air temperature for operation | -20...185 °F           |
| product certifications                | CE<br>CSA<br>UL listed |

### Offer Sustainability

|  |  |
|--|--|
| Not Green Premium product  | Not Green Premium product  |
| Will not be Compliant  | Will not be Compliant  |
| Reference not containing SVHC above the threshold  | Reference not containing SVHC above the threshold  |
| Available  | Available  |
| Need no specific recycling operations  | Need no specific recycling operations  |
| WARNING: This product can expose you to chemicals including:   | WARNING: This product can expose you to chemicals including:   |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.