

DETAILS


Product Number	FP13030_LISA2-M-CLIP
Family	Lisa2
Type	Assembly
Color	black
Diameter	9.9 mm
Height	6.8 mm
Style	round
Optic Material	PMMA
Holder Material	PC
Fastening	clips, glue
Status	ready
ROHS Compliant	Yes
Date Updated	18/08/2014




OPTICAL PROPERTIES


LED	Viewing	Light	Effi-		Connector
	Angle	Beam	ciency	cd/lm	
LUXEON H50-2	sim: 24	Medium	sim: 89 %	sim: 3.100	-
SFH 4715S (IR)	22 deg	Medium	-	sim: 0.000	-
SFH4725s (IR)	23 deg	Medium	-	sim: 0.000	-
NCSxx19B	23 deg	Medium	85 %	4.100	-
XP-G2	25 deg	Medium	89 %	3.500	-
LUXEON TX	26 deg	Medium	88 %	3.380	-
LH351Z	26 deg	Medium	87 %	3.500	-
XT-E	26 deg	Medium	89 %	3.260	-
H35C1 (LEMWA33)	28 deg	Medium	88 %	3.100	-
LUXEON T	28 deg	Medium	87 %	2.700	-

Relative intensity of FP13030&FP13028_LISA2-M_SFIR-IR



Relative intensity of FP13030_LISA2-M-CLIP_(SFH4725S)





This drawing is our property.
It can't be reproduced
or communicated without
our written agreement.



Ledil Oy
Salorankatu 10
FIN-24240 SALO
Finland

DRAWING TITLE

Datasheet Lisa2-clip16-XT series Assy

DRAWN BY

pl

DATE

20.06.2012

CHECKED BY

sn

DATE

20.7.2011

DESIGNED BY

pl

DATE

20.06.2012

SIZE

A4

DRAWING NUMBER

REV

1

SCALE


4:1

WEIGHT (g)


SHEET

1/1


Luminaire: Ledil Oy FP13030_LISA2-M-CLIP_(NCSxx19B) Efficiency=85%
Lamps: 1 x Nichia NCSxx19B (NCSL119BE) 88lm @ 250mA CCT=3000K P=0.8W I=250mA




Luminaire: LEDiL Oy FP13028&FP13030_LISA2-M_(XP-G2) Eff. 89%
Lamps: 1 x Cree_(XP-G2) 104lm@250mA CCT=6600K P=0.76W I=250mA




Luminaire: Ledil Oy FP13030_LISA2-M-CLIP_(Luxeon_TX) Efficiency=88%
Lamps: 1 x Luxeon TX (L1T2-3585) 108lm @ 250mA CCT=3521K P=0.73W I=250mA




Luminaire: Ledil Oy FP13030_LISA2-M-CLIP_(LH351Z) Efficiency=87%
Lamps: 1 x Samsung LH351Z (90.14lm @ 250mA) CCT=6500K P=0.7W I=250mA




Luminaire: LEDiL Oy FP13030&FP13028_LISA2-M_PIN&CLIP Ef. 89%
Lamps: 1 x Cree XT-E 104lm@250mA CCT=5000K P=0.77W I=250mA




Luminaire: Ledil Oy FP13030_LISA2-M-CLIP_(3535_Ceramic_gen2) Efficiency=88%
Lamps: 1 x LG 3535 Ceramic gen2 (PKG5700K) 116lm @ 250mA CCT=6200K P=0.7W I=250mA




Luminaire: LEDiL Oy FP13030&FP13028_LISA2-M_(CLIP&PIN) Eff.86.6%
Lamps: 1 x LUXEON_T (74lm@250mA)




Luminaire: Ledil Oy FP13030_LISA2-M-CLIP_(NCSxx19B) Efficiency=85%
Lamps: 1 x Nichia NCSxx19B (NCSL119BE) 88lm @ 250mA CCT=3000K P=0.8W I=250mA




Luminaire: LEDiL Oy FP13028&FP13030_LISA2-M_(XP-G2) Eff. 89%
Lamps: 1 x Cree_(XP-G2) 104lm@250mA CCT=6600K P=0.76W I=250mA



Luminaire: Ledil Oy FP13030_LISA2-M-CLIP_(Luxeon_TX) Efficiency=88%
Lamps: 1 x Luxeon TX (L1T2-3585) 108lm @ 250mA CCT=3521K P=0.73W I=250mA




Luminaire: Ledil Oy FP13030_LISA2-M-CLIP_(LH351Z) Efficiency=87%
Lamps: 1 x Samsung LH351Z (90.14lm @ 250mA) CCT=6500K P=0.7W I=250mA




cd/klm

— C0 - C180 — C90 - C270


Luminaire: LEDiL Oy FP13030&FP13028_LISA2-M_PIN&CLIP Ef. 89%
Lamps: 1 x Cree XT-E 104lm@250mA CCT=5000K P=0.77W I=250mA



Luminaire: Ledil Oy FP13030_LISA2-M-CLIP_(3535_Ceramic_gen2) Efficiency=88%
Lamps: 1 x LG 3535 Ceramic gen2 (PKG5700K) 116lm @ 250mA CCT=6200K P=0.7W I=250mA



Luminaire: LEDiL Oy FP13030&FP13028_LISA2-M_(CLIP&PIN) Eff.86.6%
Lamps: 1 x LUXEON_T (74lm@250mA)



NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.