## **Detailed Specifications & Technical Data**



ENGLISH MEASUREMENT VERSION

## AX101852 Modular Connectors - Termination Station

		(		For more Information please call 1-800-Belden1
escription:				
Fermination Station				
lsage (Overall)				
Suitable Applications:		Terminate 10GX, CAT6+, Cat5E MDVO and Keyconnect Style Module, Mediaflex Gigaflex Inserts		
Related Parts:		10GX, CAT6+, Cat5E MDVO and Keyconnect Style Module, Mediaflex Gigaflex Inserts		
hysical Characteristics (Co	nnectivity)			
Dimensions: Height (in.) Width (in.) Depth (in.) 2.500 5.600 7.000 Materials Materials: Description Material Termination Station Plastic - UL940	V-0			
Color				
Color:		Black		
Weight Weight:		0.100 lbs.		
Packaging Packaging:		Individually package units	d in a clear plastic bag, §	Standard shipping carton of 10
lechanical Characteristics (	Connectivity)			
Storage Temperature Range:		-40°C To +70°C		
Installation Temperature Range	<b>):</b>	-10°C To +60°C		
pplicable Specifications and Suitability Suitability - Indoor:		liance (Overall) Yes - Indoor		
ransmission Characteristics	s (Connectivity)			
otes (Overall)	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
Notes: For proper installation ref	er to Installation Guid	le PX103206 availat	le on our web site at http	://www.belden.com
Product Family				
ut Ups and Colors:				
tem # Putup Ship	Weight Col	or Notes	Item Desc	
AX101852 1 EA 0.333	LB BLA			

Revision Number: 0 Revision Date: 06-05-2009

© 2012 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not



## ENGLISH MEASUREMENT VERSION

## AX101852 Modular Connectors - Termination Station

ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.