XZCC8FCM30S



Main

Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Elbowed female connector M8, 3 pins
Collar material	Metal
Status LED	Without
Cable connection	Solder terminal / wire size <= 0.25 mm ² / clamping capacity <= 0.2 in (5 mm)

Complementary

Cable gland type	M9.5
Cable connector fixing	Screw-on
System Voltage	60 V AC 75 V DC
Line Rated Current	4 A
Enclosure material	Plastic
Insulating resistance	>1 GΩ
Contact resistance	<= 5000 μOhm
Product weight	0.02 lb(US) (0.01 kg)
-	

Environment

IP degree of protection	IP67	9
ambient air temperature for operation	-40185 °F (-4085 °C)	1001


Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0545 - Schneider Electric declaration of conformity	Compliant - since 0545 - Schneider Electric declaration of conformity
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Stat of California to cause birth defects or other reproductive harm.	reDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov
Contractual warranty	

18 months

Dimensions

Warranty period



(1) Cable gland: M9.5 x 1

Connections and Schemes

