





PART NO. : TG110-S050N1RL

16PIN SMT ISOLATION MODULE FOR 10/100BASE-TX
IEEE802.3u APPLICATIONS


LEAD-FREE/RoHS COMPLIANT

COMPATIBLE TO LEAD-FREE SOLDERING PROCESS
CONDITION PER IPC/JEDEC J-STD-020C

OPERATING TEMPERATURE 0/+70°C



DIMENSIONS: Inch [mm]
CO-PLANARITY: 0.004 [0.10]
TOLERANCES: ±0.005 INCH IF NOT SPECIFIED



ELECTRICAL SPECIFICATIONS @25° C

URNS RATIO	
P1-16:P8-9	1CT:1CT ±3%
OCL (100KHz,0.1Vrms,8mA)	
P1-16	350μH min
DCR P1-16	0.9Ω max
LL P1-16	0.4μH max
Cw/w	35pF max
INSERTION LOSS	
0.1-100MHz	-1.1dB max
RETURN LOSS	
0.5-30MHz	-18dB min
40MHz	-15.5dB min
50MHz	-13.6dB min
60-80MHz	-12dB min
CMR 0.1-100MHz	-35dB typ
ISOLATION	1,500Vrms

HALO/PBL

CALIFORNIA, USA
KOWLOON, HONG KONG
SINGAPORE

TITLE ISOLATION TRANSFORMER

FOR FAST ETHERNET

PART NO. TG110-S050N1RL

SCALE NONE

PAGE 1 OF 2

SIGNATURES

DRAWN PETER LU

CHECKED

APPROVED


FILE S050N1RL.DWG

DATE

2/16/06

REV.

A



RECOMMENDED SOLDER PAD DIMENSIONS
 DIIMENSIONS: Inch [mm]

HALO/PBL

CALIFORNIA, USA
 KOWLOON, HONG KONG
 SINGAPORE

TITLE	ISOLATION TRANSFORMER		SIGNATURES		DATE	REV.		
	FOR FAST ETHERNET		DRAWN PETER LU		2/16/06	A		
	PART NO. TG110-S050N1RL		CHECKED					
			APPROVED					
SCALE	NONE	PAGE	2 OF 2		FILE	S050N1RL.DWG		