



LEOPARD IMAGING INC

LI-USB30-M034WDRB

Data Sheet

Overview

Leopard Imaging USB 3.0 camera is new generation super speed USB Video camera which supports more than 3G video bandwidth to stream 720p 55fps video without compression, it provides sharper and high quality images for scientific and medical industries, Global shutter camera can support high speed conveyor line for machine vision application, lossless image quality and low latency streaming is great for video conference camera industry.

Applications

- Machine Vision
- Medical Camera
- Video Conference
- Scientific Camera



Key Features

- USB 3.0 Super Speed support
- YUV or RAW data output without compression
- UVC compliance
- USB 2.0 backwards compatible
- Support CS lens (Not include Lens)
- Provide customization services
- Support WDR
- USB +5VDC powered device

SDK Supported

- Camera Tool Source Code in C#
- Capture & Display



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035, USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email: sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

Specification

General Behavior	
Video Resolution @ Frame rate	1280 x 960 @ 30 fps, WDR 1280 x 960 @ 15 fps, WDR 1280 x 960 @ 10 fps, WDR 1280 x 720 @ 55 fps, WDR 1280 x 720 @ 30 fps, SDR 1280 x 720 @ 10 fps, WDR 640 x 480 @ 30 fps, SDR 640 x 480 @ 20 fps, SDR 640 x 480 @ 10 fps, SDR
Sensitivity	TBD
Dynamic range	12 bit
Interface (Optical)	
IR cut filter	Yes
Sensor specification	Aptina MT9M034 720p HD Sensor
Shutter	Rolling
Format	1/3"
Resolution	H:1280, V:960
Pixel size	H:3.75 um, V: 3.75 um
WDR	Support WDR (Wide Dynamic Range)
Lens mount	CS lens mount support
Interface (Electrical)	
Interface	USB 3.0
Supply voltage	USB 3.0 +5 VDC power source
Current consumption	Approx. 220 mA at 5 VDC
Interface (Mechanical)	
Dimensions	L: 30 mm, W: 30 mm, H: 30 mm
Mass (without lens)	30 g
Adjustment (Manual)	
Shutter	TBD
Gain	TBD
Adjustment (Auto)	
Shutter	TBD
Gain	TBD
Environmental	
Max. temperature (operation)	0 °C ~ 50 °C (32 °F~ 122 °F)
Max. temperature (storage)	-20 °C ~ 80 °C (-4 °F~176 °F)
Max. humidity (operation)	20 % ~ 80 %, relative, non-condensing
Max. humidity (storage)	20 % ~ 80 %, relative, non-condensing



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035, USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email: sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com