## Non-Dimming Incandescent Indicators



T-1 3/4 MIDGET FLANGE BASE

See lamp ratings on page J.

ONE TERMINAL — FULLY INSULATED for use on grounded circuits.

## FOR FRONT MOUNTING IN 15/32" CLEARANCE HOLE

MEET OR EXCEED ENVIRONMENTAL AND OPERATIONAL REQUIREMENTS
OF MIL-L-7806 AND MIL-L-3661

## **MATERIALS AND FINISHES**


- Mounting Bushing: Standard—Brass, black nickel finish.
   Optional—Polished chrome or white nickel finish.
- Mounting Nut: Brass, white nickel finish.
- Internal-tooth Lockwasher: Phosphor bronze, white nickel finish.
- Terminals: Soldering— Brass, hot tin dip.
   Screw— Brass, cadmium plated with yellow iridescent chromate finish.
- Insulation: Per MIL-L-7806.

## How to designate the Three Digit Part Number Suffix (-XXX)

Finish	Resistor	Hardware
1-white nickel 2-black nickel 3-polished chrome	0-none	1—brass 3—water-tight on the face of the panel 7—insulated mtg.*

**Example:** 8-1830-0111-101 (white nickel finish, no resistor, brass hardware).

\*For 2 terminal requirements, assembly is supplied with 2 insulating washers and a lug. Mounting hole becomes 9/16".



Part numbers listed in this catalog designate products with RED lens. For ordering lens colors other than red, consult chart on page 4C.

Order complete with lamp to be assured of receiving the indicator light and correct lamp together for immediate use.