NOTES:	THIRD ANGLE PROJ. 🕀 🚭
I. MATERIALS AND FINISHES: BODY & CONTACT - BeCu, GOLD PLATING INSULATOR - PTFE, NATURAL	REV DESCR A RELEASE
2. ELECTRICAL: A. IMPEDANCE: 50 OHM B. FREQUENCY RANGE: DC - 40 GHz C. VSWR: 1.15:1 MAX @ DC - 10 GHz 1.25:1 MAX @ 10 - 26.5 GHz 1.35:1 MAX @ 26.5 - 40 GHz D. DIELECTRIC WITHSTANDING VOLTAGE: 500 VRMS, MIN.	
3. MECHANICAL: A. DURABILITY: IOO CYCLES MIN. B. TEMPERATURE RANGE: -65°C TO I65°C	
4. PACKAGING: A. QUANTITY: SINGLE PACK B. MARKING: BAG TO BE MARKED "AMPHENOL RF, 925-141A-51S, AND DATE CODE"	
	► Ø 2.72 [0.107]

-Ø2.23 REF [0.088] TYP(2)

С	U	8	Т	C	
			-		_

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: <0.5mm 0.5 - 6mm 6 - 30mm 30 - 120mm ANGLES ±0.05mm ±0.1mm ±0.2mm ±0.3mm ±1°	MATERIAL SEE NOTES	DRAWN E WANKOFF	DATE II-Jan-I3	TITLE SMPM_STR_BULLET	Amphenol RF
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they	- SEL NUTES	ENGINEER E WANKOFF	DATE II-Jan-I3	JACK TO JACK ASSEMBLY	www.amphenolrf.com
are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any	REFERENCE EAR # 5420	APPROVED K. CAPOZZI	DATE 4-Dec- 6	- 0.278" LONG SCALE: 30.0:1.0 SHEET 2 OF 2	DRAWING NO.925-141A-51S ITEM NO.925-141A-51S
product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	CONFIGURATION LEVEL: In Work FINISH	CAD FILE		dwg size rev B A	PART NO. 925-141A-51S

REVISI PTION	ONS	D	ATE	ECO	APPR
TO MFG.			Dec-16	02642	BMG
			SCA	LE 7.00	0
REF					
		\mathbb{N}	$\langle \rangle \rangle$		
	\bigcirc	<u>}</u>))		
				//	

