

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [1552200291](#)  
**Status:** **Active**  
**Overview:** [Flamar Standard Cables for Industrial Automation](#)  
**Description:** Flamar Control Cable, WSOR Jacket, Unshielded, 5 Circuits, 14 AWG with Green/  
 Yellow Ground, 11.30mm Diameter, 1000.0m Length, Black

**Documents:**

[RoHS Certificate of Compliance \(PDF\)](#)

[Product Literature \(PDF\)](#)

**General**

Product Family	Cable
Series	<a href="#">155220</a>
Bending Radius - Minimum	> 7.5xOD
Color - Cable Jacket	Black
Crimp Quality Equipment	Yes
Geographic Area	Global
Material - Outer Jacket	WSOR
Outer Jacket Diameter	11.30mm (.445")
Overview	<a href="#">Flamar Standard Cables for Industrial Automation</a>
Product Literature Order No	987651-3992
Product Name	Flamar
UPC	889056462457

**Physical**

Cable Length	1000.0m
Circuits (Loaded)	5
Insulation	TPE
Net Weight	0.010/g
Packaging Type	Wooden Drum
Temperature Range - Operating	-25°C to +80°C
Wire Size AWG	14
Wire Size mm <sup>2</sup>	2.50
Wire/Cable Type	Signal and Control, UL AWM 21215 / CSA

**Electrical**

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	600V

**Material Info**

Old Part Number	1X1000M
-----------------	---------



*Series image - Reference only*

**EU ELV**

**Not Reviewed**

**EU RoHS**

**Not Reviewed**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

Not Reviewed

ELV

Not Reviewed

**Search Parts in this Series**

[155220](#) Series

**Use With**

DIN Valve Connectors [121201](#) ,  
[121202](#) , [121207](#) , [121208](#) , [121205](#)  
 , [121211](#) <br>Micro-Change® (M12)  
[120071](#) <br>Ultra-Lock® (M12) [120085](#)  
 <br>GWconnect® Heavy Duty Connectors  
[93601](#)

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**