

CUTE-3-SS

~12° smooth spot beam with 3 mm high location pins

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 35.0 mm
Height	15 mm
Fastening	glue, pin
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
CUTE-3-SS	Multi-lens	PMMA	clear	

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C10754_CUTE-3-SS	630	90	45	6.9
» Box size: 480 x 280 x 300 mm				







PHOTOMETRIC DATA (MEASURED):




LED XM-L
FWHM 19.0°
Efficiency 91 %
Peak intensity 5.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LED XM-L2
FWHM 20.0°
Efficiency 90 %
Peak intensity 6.4 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED XP-E
FWHM 11.0°
Efficiency 93 %
Peak intensity 15.4 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED XP-G
FWHM 15.0°
Efficiency 93 %
Peak intensity 9.5 cd/Im
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):




LED XP-G2
FWHM 14.0°
Efficiency 89 %
Peak intensity 11.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XT-E
FWHM 12.0°
Efficiency 88 %
Peak intensity 8.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED H35C1 (LEMWA33)
FWHM 14.0°
Efficiency 86 %
Peak intensity 10.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON A
FWHM 13.0°
Efficiency 91 %
LEDs/each optic 1
Light colour White
Required components:

PHOTOMETRIC DATA (MEASURED):



LED LUXEON Rebel
FWHM 12.0°
Efficiency 91 %
Peak intensity 12.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON Rebel ES
FWHM 13.0°
Efficiency 91 %
LEDs/each optic 1
Light colour White
Required components:



LED NCSxx19A
FWHM 12.0°
Efficiency 89 %
LEDs/each optic 1
Light colour White
Required components:



LED NVSxx19A
FWHM 13.0°
Efficiency 94 %
Peak intensity 9.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):

OSRAM


Opto Semiconductors

LED OSLON Square EC
FWHM 17.0°
Efficiency 83 %
Peak intensity 8.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:

OSRAM

Opto Semiconductors


LED OSLON SSL 150
FWHM 13.0°
Efficiency %
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors

LED OSLON SSL 80
FWHM 10.0°
Efficiency 90 %
Peak intensity 15.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SEOUL

SEOUL SEMICONDUCTOR

LED Z5
FWHM 10.0°
Efficiency %
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (MEASURED):



PHOTOMETRIC DATA (SIMULATED):

CREE

LED	XM-L HVW
FWHM	19.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	

CREE

LED	XT-E HVW
FWHM	15.0°
Efficiency	%
LEDs/each optic	1
Light colour	White
Required components:	

SAMSUNG

LED	LH351B
FWHM	16.0°
Efficiency	95 %
Peak intensity	8.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)