

Cable
 LIYY 2x0,25 mm², grey
 colour of wires: white and brown
 ends tinned
 LIYY 2x0,25 mm², grau
 Aderfarben: weiss und braun
 Enden verzinkt

Nut
 M10, DIN 439 B, stainless steel, ws 17
 M10, DIN 439 B, Edelstahl, SW 17

O-ring
 NBR, black
 NBR, schwarz

Stem
 stainless steel
 Edelstahl

Float
 MS09-S, stainless steel
 MS09-S, Edelstahl

Two-ear clamp
 stainless steel
 Zweiohrklemme, Edelstahl

Dimensions mm[inch]

tolerances acc. to DIN ISO 2768-m
 Toleranzen gem. DIN ISO 2768-m

Schematic

OPEN
OFFEN

CLOSED
GESCHLOSSEN

Isometric
 Scale 1:2
 Maßstab 1:2

Marking
 according to EN60062/factory code
 gem. EN60062/Fertigungsstätte

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			100	W
Switching voltage	DC or Peak AC			250	V
Carry current	DC or Peak AC			2,5	A
Switching current	DC or Peak AC			1	A
Sensor-resistance	measured with 40% overdrive			280	mOhm
Breakdown voltage		1			kV DC
Insulation Voltage	Case/Contact	1			kV DC
Material of float				stainless steel	
Housing material LS				stainless steel	
Sealing compound				Polyurethan	

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	cable not moved	-30		80	°C
Operating temperature	cable moved	-5		80	°C
Storage temperature		-30		80	°C
Safety class	DIN EN 60529			IP68	

Cable specification	Conditions	Min	Typ	Max	Unit
Cable type				round cable	
Cable material				PVC	
Cross section				0,25 sq-mm	

General data	Conditions	Min	Typ	Max	Unit
Mounting advice				over 5m cable, a resistor is recommended.	
Tightening torque				5	Nm