

# Product: <u>6501UE</u> ☑

# Security & Sound, 3 Conductor 22 AWG BC, Plenum



# **Product Description**

Security & Commercial Audio Cable, 3 Conductor 22 AWG stranded (7x30) bare copper conductors with Flamarrest® insulation, Plenum, Flamarrest® jacket with ripcord.

# **Technical Specifications**

Suitable Applications:			Intercom/PA Systems, Sound/Audio Systems				
Phys	ical Char	acteristics (O	verall)				
Condu	ictor						
AWG			No. of Conducto	rs			
22 7x30 BC - Bare Copper 3			r 3				
Condu	uctor Count:			3			
nsulat	tion						
nsulat		aterial	Material Trac	le Name	Nominal Wall Thic	kness	
PVC-L		I Chloride (Low Sm			0.009 in		
2							
3	Red White Shield Mater	rial					
3 Duter \$ Mater No Sh	White Shield Mater rial nield Jacket Mater		Material Trad	e Name	Nominal Diameter	Nominal Wall Thickness	Ripco
3 Duter \$ Mater No Sh Duter \$	White Shield Mater rial jield Jacket Mater Mater S - Polyviny	rial	Material Trad		Nominal Diameter 0.131 in	Nominal Wall Thickness 0.015 in	Ripcol Yes
3 Duter 9 Mater No Sh Duter 0 Smoke Cons Cabline Twis 4.8 tw	White Shield Mater rial Jacket Mater M LS - Polyviny e) Struction g sts ist/ft	rial aterial	Flamarrest®				
3 Mater No Sh Duter , PVC-L Smoku Cons Cabling Twis Cabling Twis Cabling Cabli	White Shield Mater rial jacket Mater M LS - Polyviny e) struction g sts ist/ft trical Cha	rial aterial I Chloride (Low and Dimension racteristics	Flamarrest®				
3 Mater No Sh Duter , Smoke Cons Cabling Twis 4.8 tw Elect Condu	White Shield Mater rial jacket Mater M LS - Polyviny e) etruction g sts rist/ft trical Cha	rial aterial I Chloride (Low and Dimension racteristics	Flamarrest®				

#### Current

Max. Recommended Current [A] 2.8 Amps per Conductor at 25°C

#### Voltage

UL Voltage Rating 300 V RMS

## **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

### **Mechanical Characteristics**

Bulk Cable Weight:	13.3 lbs/1000ft
Max. Pull Tension:	27.3 lbs
Min Bend Radius/Minor Axis:	1.3 in

#### **Standards**

NEC Articles:	Article 800
NEC/(UL) Compliance:	СМР
CEC/C(UL) Compliance:	СМР

#### **Applicable Environmental and Other Programs**

Environmental Space:	Indoor - Plenum
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

#### Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262
UL voltage rating:	300 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N):	Yes	
Part Number		
Non-Plenum Number:	5501UE	

## Non-Plenum Number:

# Variants

ltem #	Color	Putup Type	Length	UPC
6501UE 8771000	Natural	Reel	1,000 ft	612825177531
6501UE 877U1000	Natural	UnReel	1,000 ft	612825424031
6501UE 877Z1000	Natural	ReelTuff Box	1,000 ft	612825177555

#### History

Update and Revision:

Revision Number: 0.267 Revision Date: 06-08-2020

#### © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.