



Main

Range of product	TeSys
Device short name	GS1AM
Product or component type	Auxiliary contact
Contact application	O, I and test position signalling
Contacts type and composition	1 NC
Contact operation	Early-break
[Ith] conventional free air thermal current	16 A at 104 °F (40 °C)
[Ie] rated operational current	3 A at 240 V AC-15 6 A at 120 V AC-15 1.5 A at 480 V AC-15 1.8 A at 400 V AC-15 2.8 A at 24 V DC-13 0.15 A at 400 V DC-13 0.27 A at 250 V DC-13 0.55 A at 125 V DC-13 1.4 A at 48 V DC-13

Complementary

Range compatibility	TeSys ,TeSys GS ,GS1 DD ,switch-disconnector-fuse
Mechanical durability	5000000 cycles
Electrical durability	1000000 cycles on AC-15
Product compatibility	GS1
Line Rated Current	1250 A 100 A 125 A 160 A 200 A 250 A 315 A 32 A 400 A 50 A 60 A 600 A 63 A 630 A 800 A
Fuse type	BS DIN NFC
Type of operating handle	External frontal External left side External right side
Product weight	0.03 lb(US) (0.015 kg)

Environment

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0701 - Schneider Electric declaration of conformity	Compliant - since 0701 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
WARNING: Cancer - www.P65Warnings.ca.gov	WARNING: Cancer - www.P65Warnings.ca.gov

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Auxiliary Contacts - 1 N/C

