


# PIN RECEPTACLES

**FOR 0,64 - 0,94 DIAMETER PINS AND 0,64 SQUARE PINS**

## 0401/6401

**X401-0-15-XX-47-XX-04-0**

Press-fit in 1,63 mounting hole




| Basic Part Number | Length A |
|-------------------|----------|
| <b>0401-0</b>     | 8,64     |
| <b>6401-0</b>     | 13,72    |

## 1303

**1303-0-15-XX-47-XX-04-0**


Press-fit in 1,55 mounting hole



## 8303

**8303-0-15-XX-47-XX-04-0**


Press-fit in 1,55 mounting hole



## 4095

**4095-0-15-XX-47-XX-04-0**

Press-fit in 1,55 mounting hole




## 8806

**8806-0-18-XX-47-XX-40-0**


Surface mount

Also available on 12mm wide carrier tape:  
4,000 parts per 330mm reel

Order as: 8806-0-58-XX-47-XX-10-0




P.C.B. Layout



## 0722

**0722-0-33-XX-47-XX-10-0**

Wire crimp termination. Accepts wire  
sizes 22 AWG Max. / 28 AWG Min.



### SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Millimeters

**Tolerances On:** Lengths:  $\pm 0,13$   
Diameters:  $\pm 0,051$   
Angles:  $\pm 2^\circ$



**ORDER CODE: XXXX - X - 1X - XX - 47 - XX - XX - 0**

**BASIC PART #**

**SPECIFY SHELL FINISH:**

- 01** 5,08 $\mu$ m TIN/LEAD OVER NICKEL
- 80** 5,08 $\mu$ m TIN OVER NICKEL (RoHS)
- 15** 0,25 $\mu$ m GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

- 01** 5,08 $\mu$ m TIN/LEAD OVER NICKEL
- 80** 5,08 $\mu$ m TIN OVER NICKEL (RoHS)
- 27** 0,76 $\mu$ m GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#47** CONTACT (DATA ON PAGE 256)

(For alternate contact choices, see group D on page 248)



Mill-Max Mfg. Corp. • 190 Pine Hollow Road, P.O. Box 300, Oyster Bay, NY 11771 • 516-922-6000 • Fax: 516-922-9253 • www.mill-max.com