Quick Reference

Search by part #

Check distributor part inventory

Products

Browse Products

-By Device -

-By Product Line-

-Attachment Methods

-Interface Materials-

-Accessories -

Useful Links

MSDS Safety Sheets
How to Order?
Find Sales Rep
Find Distributor
Sample Request
Quote Request
Catalog Request
Building a Part #
Part # Cross Ref

Accessories

Standard Mounting Pads

The following Mounting Pads are for use with TO-18

7717-157TG

RoHS ✓ Compliant

(Teflon)

Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 0.25 (0.010)



7717-153DAPG

RoHS ✓ Compliant

(DAP)

Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 0.97 (0.038)



7717-153NG

RoHS ✓ Compliant

(nylon)

Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 0.97 (0.038)



7717-152DAPG

RoHS ✓ Compliant

(DAP)

Leads: 4-Mar

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 1.14 (0.045)



7717-152NG

RoHS ✓ Compliant

(nylon)

Leads: 4-Mar

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 1.14 (0.045)



7717-124NG

RoHS ✓ Compliant

(nylon)

Leads: 4

Outside Diameter mm (in): 5.72 (0.225)

Thickness: 0.51 (0.020)



7717-7DAPG

RoHS ✓ Compliant | Product Change Notice

(DAP)

Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 3.18 (0.125)



7717-7NG

RoHS ✓ Compliant | Product Change Notice

(nylon)

Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 3.18 (0.125)



7717-89DAPG

RoHS ✓ Compliant | Product Change Notice

(DAP)

Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 2.03 (0.080)



7717-89NG

RoHS ✓ Compliant | Product Change Notice

(nylon)

Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 2.03 (0.080)



7717-108DAPG

RoHS ✓ Compliant | Product Change Notice

(DAP)

Leads: 4

Outside Diameter mm (in): 5.26 (0.203)

Thickness: 1.78 (0.070)



7717-108NG

RoHS ✓ Compliant | Product Change Notice

(nylon)

Leads: 4

Outside Diameter mm (in): 5.26 (0.203)

Thickness: 1.78 (0.070)



7717-18DAPG

RoHS ✓ Compliant | Product Change Notice

(DAP)

Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 2.54 (0.100)



7717-18NG

RoHS ✓ Compliant | Product Change Notice

(nylon)

Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 2.54 (0.100)



7717-16NG

RoHS ✓ Compliant | Product Change Notice

(nylon)

Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 0.51 (0.020)



7717-16DAPG

RoHS ✓ Compliant | Product Change Notice

(DAP)

Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 0.51 (0.020)



7717-112DAPG

RoHS ✓ Compliant

(DAP)

Leads: 4-Mar

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 0.64 (0.025)



7717-220NG

RoHS ✓ Compliant

(nylon)

Leads: 4-Mar

Outside Diameter mm (in): 5.84 (0.230)

Thickness: 2.03 (0.080)



7717-239NG

RoHS ✓ Compliant

(nylon)

Leads: 4-Mar

Outside Diameter mm (in): 6.10 (0.240)

Thickness: 457 (0.180)



7717-46NG

RoHS ✓ Compliant

(nylon)

Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 1.52 (0.060)



7717-46DAPG

RoHS ✓ Compliant

(DAP)

Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 1.52 (0.060)