Quick Reference

Search by part #

Check distributor part inventory

Products

Browse Products

-By Device -

-By Product Line-

-Attachment Methods

-Interface Materials-

-Accessories -

Useful Links

MSDS Safety Sheets
How to Order?
Find Sales Rep
Find Distributor
Sample Request
Quote Request
Catalog Request
Building a Part #
Part # Cross Ref


Accessories

Standard Mounting Pads

The following Mounting Pads are for use with TO18

7717-157TG

RoHS Compliant



(Teflon)


Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 0.25 (0.010)

7717-153DAPG

RoHS Compliant



(DAP)


Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 0.97 (0.038)

7717-153NG

RoHS Compliant



(nylon)


Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 0.97 (0.038)

7717-152DAPG

RoHS Compliant



(DAP)


Leads: 4-Mar

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 1.14 (0.045)

7717-152NG

RoHS Compliant



(nylon)


Leads: 4-Mar

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 1.14 (0.045)

7717-124NG

RoHS Compliant



(nylon)


Leads: 4

Outside Diameter mm (in): 5.72 (0.225)

Thickness: 0.51 (0.020)

7717-7DAPG

RoHS Compliant | Product Change Notice



(DAP)


Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 3.18 (0.125)

7717-7NG

RoHS Compliant | Product Change Notice



(nylon)


Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 3.18 (0.125)

7717-89DAPG

RoHS Compliant | Product Change Notice



(DAP)


Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 2.03 (0.080)

7717-89NG

RoHS Compliant | Product Change Notice



(nylon)


Leads: 4

Outside Diameter mm (in): 6.35 (0.250)

Thickness: 2.03 (0.080)

7717-108DAPG

RoHS Compliant | Product Change Notice



(DAP)


Leads: 4

Outside Diameter mm (in): 5.26 (0.203)

Thickness: 1.78 (0.070)

7717-108NG

RoHS Compliant | Product Change Notice



(nylon)


Leads: 4

Outside Diameter mm (in): 5.26 (0.203)

Thickness: 1.78 (0.070)

7717-18DAPG

RoHS Compliant | Product Change Notice



(DAP)


Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 2.54 (0.100)

7717-18NG

RoHS Compliant | Product Change Notice



(nylon)


Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 2.54 (0.100)

7717-16NG

RoHS Compliant | Product Change Notice



(nylon)


Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 0.51 (0.020)

7717-16DAPG

RoHS Compliant | Product Change Notice



(DAP)


Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 0.51 (0.020)

7717-112DAPG

RoHS Compliant



(DAP)


Leads: 4-Mar

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 0.64 (0.025)

7717-220NG

RoHS Compliant



(nylon)


Leads: 4-Mar

Outside Diameter mm (in): 5.84 (0.230)

Thickness: 2.03 (0.080)

7717-239NG

RoHS Compliant



(nylon)


Leads: 4-Mar

Outside Diameter mm (in): 6.10 (0.240)

Thickness: 457 (0.180)

7717-46NG

RoHS Compliant



(nylon)


Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 1.52 (0.060)

7717-46DAPG

RoHS Compliant



(DAP)

Leads: 4

Outside Diameter mm (in): 5.08 (0.200)

Thickness: 1.52 (0.060)