

# Interface module - UM45-D37SUB/M/F/SC072 - 2907911


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE termination board, with a 37-pos. D-SUB socket strip to a 37-pos. D-SUB pin strip, 1:1 connection



## Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 055626 256504
GTIN	4055626256504

## Technical data

### Dimensions

Width	66 mm
Height	45 mm
Depth	50 mm

### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
---------------------------------	------------------

### General

Max. perm. operating voltage	25 V AC (60 V DC)
Max. perm. current (per branch)	2.5 A
Mounting position	any
Degree of protection	IP00

### Connection data for connection 1

Connection name	D-SUB connection
Connection method	D-SUB socket strip
Number of connections	1
Number of positions	37

## Interface module - UM45-D37SUB/M/F/SC072 - 2907911

### Technical data

#### Connection data for connection 2

Connection name	D-SUB connection
Connection method	D-SUB pin strip
Number of connections	1
Number of positions	37

#### Standards and Regulations

Designation	Air clearances and creepage distances
Standards/regulations	DIN EN 50178: 1998-04
Rated insulation voltage	50 V
Rated surge voltage	0.5 kV (1.2/50 $\mu$ s)
Insulation	Functional insulation
Degree of pollution	2
Overvoltage category	II

#### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>