

THIRD ANGLE PROJ.

REVISIONS

I. MATERIALS AND FINISHES:


3. PACKAGING:

BNC CRIMP PLUG - 112951-11
CABLE - BELDEN 1505A


A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 95-850-165XXXX AND DATE CODE".

2. ELECTRICAL:

A. IMPEDANCE: 75 OHM



LENGTH TABLE		
PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH "L" IN INCHES [METERS]
95-850-165-006	-	6.00 [0.152]
	95-850-165M025	9.84 [0.250]
95-850-165-012	-	12.00 [0.305]
95-850-165-018	-	18.00 [0.457]
-	95-850-165M050	19.69 [0.500]
95-850-165-024	-	24.00 [0.610]
-	95-850-165M075	29.53 [0.750]
95-850-165-036		36.00 [0.914]
-	95-850-165M100	39.37 [1.000]
95-850-165-048	-	48.00 [1.219]
-	95-850-165M125	49.21 [1.250]
-	95-850-165M150	59.06 [1.500]
95-850-165-060	-	60.00 [1.524]
95-850-165-072	-	72.00 [1.829]
-	95-850-165M200	78.74 [2.000]
-	95-850-165M300	118.11 [3.000]
95-850-165-120	-	120.00 [3.048]
95-850-165-180	-	180.00 [4.572]
	95-850-165M500	196.85 [5.000]
95-850-165-300		300.00 [7.620]
-	95-850-165M10L	393.70 [10.000]
95-850-165L050	-	600.00 [15.240]
-	95-850-165M20L	787.40 [20.000]
95-850-165L075	-	900.00 [22.860]
-	95-850-165M30L	1181.10 [30.000]
95-850-165L100	-	1200.00 [30.480]



SCALE 0.750

DESIGN REQUIREMENTS:

X FREQUENCY: DC TO 4 GHz

X CONTINUITY

VSWR MAX

X HI-POT : 500 VRMS

INS. LOSS ----- dB MAX

☐ OTHER

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:

2 PLACE DECIMAL	3 PLACE DECIMAL	ANGLES
±.015 (0,381 mm)	±.005 (0,127 mm)	± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL

SEE NOTES

REFERENCE
EAR # 6516

CONFIGURATION LEVEL: In Work

FINISH

DRAWN	DATE
MADHAN G	10-Dec-14

DATE
10-Dec-14

ENGINEER	DATE
MADHAN G	10-Dec-14

DATE
10-Dec-14

APPROVED	DATE
K. CAPOZZI	5/12/15

DATE
5/12/15

CAD FILE

TITLE
BNC CRIMP PLUG TO
BNC CRIMP PLUG,
USING BELDEN 1505A CABLE,
VARIOUS LENGTH

SCALE: 3.0:1.0	SHEET 2 OF 2
----------------	--------------

DWG SIZE
B

REV
A

Amphenol RF

www.amphenolrf.com

DRAWING NO. 95-850-165XXXX

ITEM NO. 95-850-165XXXX

PART NO. 95-850-165XXXX

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY