



RECEPTACLE HOLDER

PLUG HOLDER

| Shell Size | Max. Recommended Torque (Inch Pounds) | A Dia. Max. | B Dia. Max. | C Dim. Max. |
|------------|---------------------------------------|--------------|--------------|--------------|
| 08 | 60 | .537 (13.6) | .424 (10.8) | 1.031 (26.2) |
| 10 | 80 | .660 (16.8) | .526 (13.4) | 1.031 (26.2) |
| 12 | 110 | .830 (21.1) | .696 (17.7) | 1.031 (26.2) |
| 14 | 120 | .899 (22.8) | .765 (19.4) | 1.031 (26.2) |
| 16 | 120 | 1.026 (26.1) | .892 (22.7) | 1.031 (26.2) |
| 18 | 120 | 1.132 (28.8) | .998 (25.3) | 1.031 (26.2) |
| 20 | 140 | 1.259 (32.0) | 1.123 (28.6) | 1.031 (26.2) |
| 22 | 140 | 1.382 (35.1) | 1.248 (31.7) | 1.031 (26.2) |
| 24 | 140 | 1.509 (38.3) | 1.373 (34.9) | 1.031 (26.2) |
| 28* | 150 | 1.740 (44.2) | 1.623 (41.2) | 1.031 (26.2) |

* Non-Military standard shell size

APPLICATION NOTES

- Metric dimensions (mm) are indicated in parentheses.
- Material: Case hardened carbon steel with electroless nickel finish.
- Receptacle and plug holder drives: 1/4" - Shell sizes 08, 10, 12; 3/8" - Shell sizes 14 and up.