



RECEPTACLE HOLDER

PLUG HOLDER

| Shell Size | Max. Recommended Torque (Inch Pounds) | A Dia. Max.  | B Dia. Max.  | C Dim. Max.  |
|------------|---------------------------------------|--------------|--------------|--------------|
| 08         | 60                                    | .537 (13.6)  | .424 (10.8)  | 1.031 (26.2) |
| 10         | 80                                    | .660 (16.8)  | .526 (13.4)  | 1.031 (26.2) |
| 12         | 110                                   | .830 (21.1)  | .696 (17.7)  | 1.031 (26.2) |
| 14         | 120                                   | .899 (22.8)  | .765 (19.4)  | 1.031 (26.2) |
| 16         | 120                                   | 1.026 (26.1) | .892 (22.7)  | 1.031 (26.2) |
| 18         | 120                                   | 1.132 (28.8) | .998 (25.3)  | 1.031 (26.2) |
| 20         | 140                                   | 1.259 (32.0) | 1.123 (28.6) | 1.031 (26.2) |
| 22         | 140                                   | 1.382 (35.1) | 1.248 (31.7) | 1.031 (26.2) |
| 24         | 140                                   | 1.509 (38.3) | 1.373 (34.9) | 1.031 (26.2) |
| 28*        | 150                                   | 1.740 (44.2) | 1.623 (41.2) | 1.031 (26.2) |

\* Non-Military standard shell size

### APPLICATION NOTES

- Metric dimensions (mm) are indicated in parentheses.
- Material: Case hardened carbon steel with electroless nickel finish.
- Receptacle and plug holder drives: 1/4" - Shell sizes 08, 10, 12; 3/8" - Shell sizes 14 and up.