

NOTES:

1. DCC-US3AB-180 SHOWN IN EXPLODED VIEW. (USB 3.0 TYPE A WITH QUICK CONNECT COUPLING.)

MATERIALS:

PLUG HOUSING: THERMOPLASTIC
SEALING NUT, COUPLING RING: THERMOPLASTIC
SEALING RING: ELASTOMER
O-RING: ELASTOMER
INSERT: THERMOPLASTIC
USB 3.0 PLUG:
INSULATOR: THERMOPLASTIC, BLUE
CONTACTS: COPPER ALLOY, GOLD PLATED
SHIELD: STEEL, NICKEL PLATED

ELECTRICAL:

CONTACT RESISTANCE: 50 MILLIOHMS MAX
CONTACT CURRENT RATING: 1.0A DC MAX
INSULATION RESISTANCE: 100 MEGAOHMS MIN
WITHSTANDING VOLTAGE: 750V AC FOR 1 MINUTE



PRODUCT RATING:

IP67 & IP68, NEMA 250 (6P) WHEN MATED
USB A PLUG: USB 3.0


OTHER:

OPERATING TEMPERATURE: -25°C TO +80°C (-13°F TO +176°F)
RECOMMENDED CABLE TYPE: SOLID OR STRANDED CONDUCTORS
OUTER CABLE O.D. RANGE:
PRODUCT 180 SERIES: 0.171-0.208 [4.34mm-5.28mm]

PART NUMBER	PART REV	USB TYPE	COUPLING TYPE
DCC-US3AB-180	0A	USB 3.0 A	QUICK CONNECT
DCC-US3AT-180	0A	USB 3.0 A	THREADED



DCC-US3AB-180
USB 3.0 TYPE A WITH QUICK CONNECT COUPLING




DCC-US3AT-180
USB 3.0 TYPE A WITH THREADED COUPLING

DIMENSIONS IN BRACKET [] ARE METRIC.

RoHS COMPLIANT

CUSTOMER DRAWING

0A	JGK	4/24/17	DRAWING CREATED FOR PROJECT #12012.		
REV.	INIT.	DATE	DESCRIPTION		
	JGK	4/24/17	ORIG. DRAWN BY:	DATE:	 601 E. WILDWOOD VILLA PARK, IL 60181
			CHECKED BY:		
			APPROVED BY:		
ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION." UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.			SCALE	SIZE	TITLE: INDUSTRIAL USB 3.0 A PLUG FIELD INSTALLABLE DATA-CON-X CUSTOMER: STANDARD PRODUCT
ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS.			NTS	B	
UNLESS OTHERWISE SPECIFIED TOLERANCES: 3 PLACE DECIMALS ±.005 ANGLES ±1° FRACTIONS ±1/16 - CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX			FILE: DCC-US3AX SERIES_CD	DIRECTORY: SLW	
			PART NUMBER:	DCC-US3AX-180 SERIES	REV 0A

**ASSEMBLY INSTRUCTIONS:**


1. SLIDE THE O-RING ONTO THE FRONT END OF THE PLUG HOUSING UNTIL IT SEATS UP AGAINST THE RIDGE OF THE PLUG HOUSING.
2. SLIDE THE COUPLING RING OVER THE PLUG HOUSING.
NOTE: MAKE SURE THE FRONT OF THE COUPLING RING CAN SLIDE PAST THE RIDGE ON THE PLUG HOUSING. IF NOT, IT IS INSERTED THE WRONG WAY.
3. SLIDE THE SEALING NUT, SEALING RING, AND PLUG HOUSING/COUPLING RING OVER THE FRONT END OF THE CABLE IN THE FOLLOWING ORDER:
1ST. SEALING NUT.
2ND. SEALING RING.
3RD. PLUG HOUSING/COUPLING RING.
4. TERMINATE THE USB PLUG TO THE CABLE.
NOTE: SEE FIGURE 1 FOR TERMINATION GUIDE.
SEE FIGURE 2 FOR RECOMMENDED STRIPPING DETAIL.
SEE FIGURE 4 FOR TYPICAL USB 3.0 WIRING ASSIGNMENT.
5. SLIDE THE USB PLUG INTO THE BACK END OF THE INSERT UNTIL IT SNAPS INTO PLACE.
NOTE: SEE FIGURE 5 FOR INSERT AND PLUG ALIGNMENT.
6. SLIDE THE INSERT/USB PLUG INTO THE FRONT END OF THE PLUG HOUSING UNTIL IT SNAPS INTO PLACE.
7. PUSH THE SEALING RING INTO THE REAR OF THE PLUG HOUSING.
NOTE: NO PART OF THE SEALING RING SHOULD EXTEND PAST THE REAR OF THE PLUG HOUSING.
8. SCREW THE SEALING NUT ONTO THE PLUG HOUSING.

CUSTOMER DRAWING

0A		JGK	4/24/17		SEE PAGE 1.					
REV.		INIT.		DATE		DESCRIPTION				
ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION." UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.					ORIG. DRAWN BY:		DATE:			
					JGK		4/24/17			
ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS. UNLESS OTHERWISE SPECIFIED TOLERANCES: 3 PLACE DECIMALS ±.005 ANGLES ±1° FRACTIONS ±1/16 ▷ = CRITICAL CHARACTERISTIC FLAG PER SPEC, XXXX					CHECKED BY:		conxall 601 E. WILDWOOD VILLA PARK, IL 60181			
					APPROVED BY:		TITLE:			
							INDUSTRIAL USB 3.0 A PLUG FIELD INSTALLABLE DATA-CON-X			
					SCALE		SIZE		SHEET	
					NTS		B		2 OF 3	
					FILE:		DIRECTORY:		PART NUMBER:	
					DCC-US3AX SERIES_CD		SLW		DCC-US3AX-180 SERIES	
									REV 0A	

RoHS COMPLIANT

FIGURE 1



USB ASSEMBLY INSTRUCTIONS

- 1. SOLDER THE CABLE WIRES TO THE INSULATOR BODY. SEE FIGURE 2 FOR RECOMMENDED CABLE STRIPPING DETAIL AND FIGURE 3 FOR PINOUT. FIGURE 4 SHOWS THE USB 3.0 TYPICAL WIRING ASSIGNMENT.
- 2. PLACE THE INSULATOR BODY ASSEMBLY INTO THE FRONT SHELL AND PUSH FORWARD UNTIL IT SITS FIRMLY INTO THE FRONT SHELL.
- 3. SNAP THE BACK SHELL ONTO THE FRONT SHELL.
- 4. CRIMP THE BACK SHELL CLAMP AROUND THE CABLE JACKET.

FIGURE 2




FIGURE 3





FIGURE 4

TYPICAL USB 3.0 A WIRING	
PIN	CABLE COLOR
1	RED
2	WHITE
3	GREEN
4	BLACK
5	BLUE
6	YELLOW
7	DRAIN WIRE
8	PURPLE
9	ORANGE
SHIELD	BRAID

FIGURE 5



THE PLUG BODY TOP AND THE INSERT EXTERNAL FEATURE MUST BE ALIGNED.

RoHS COMPLIANT

CUSTOMER DRAWING

0A	JGK	4/24/17	SEE PAGE 1.
REV.	INIT.	DATE	DESCRIPTION
	JGK	4/24/17	ORIG. DRAWN BY: DATE: 4/24/17
			CHECKED BY:
			APPROVED BY:
			SCALE NTS SIZE B SHEET 3 OF 3
			FILE: DCC-US3AX SERIES_CD DIRECTORY: SLW
			TITLE: INDUSTRIAL USB 3.0 A PLUG FIELD INSTALLABLE DATA-CON-X CUSTOMER: STANDARD PRODUCT
			PART NUMBER: DCC-US3AX-180 SERIES REV 0A