Product datasheet Characteristics

9001SKR25GH13

			٠	
n	л	•	п	r

Bezel material	Black plastic
Device short name	К
Enclosure type	Weatherproof enclosure dust and oil resistant indoor/outdoor Enclosure corrosion resistance indoor/outdoor
Light source	Without
Mounting diameter	1.18 in (30 mm)
Operator additional information	Without guard Screw-on plastic mushroom with set screw 2.25 in

Complementary

Line Rated Current	10 A	
Cap/operator or lens colour	Green	
Contact operation	Standard fingersafe	
Contacts type and composition	1 NO + 1 NC	
Control type	Push-button	
Electrical connection	Screw clamp terminal	
Light block supply	Without supply	
Marking	Unmarked	
Mounting support	Panel	
Operator position information	2 positions	
Operator profile	1 projecting push-button	
Permissible voltage	<= 600 V	
Shape	Round head	
Type of operator	Momentary	
Utilisation category	AC-15 DC-13	
<u> </u>		

Environment

NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13
product certifications	CE UL listed file E42259 CCN NKCR
	CSA LR24590 class 3211 03

Offer Sustainability

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
Nickel compounds, which is known to the State of California to cause cancer, and	Nickel compounds, which is known to the State of California to cause cancer, and	
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm.		
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Warranty period	18 months