

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0757830310

Status:

Active

Overview:

iPass™ Connector System

Description:

iPass™ I/O Surface Mount Receptacle, Right Angle, Internal Assembly with Shell, 68 Circuit, 0.38μm Gold (Au), Surface Mount Option, Tail Length 1.96mm, Right Key



Series image - Reference only

Documents:

3D Model

Drawing (PDF)

Product Specification PS-75783-001 (PDF)

Application Specification AS-75783-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification		
CSA		LR19980
UL		E29179
General		
Product Family		I/O Connectors
Series		75783
Application		Wire-to-Board
Comments		Positive or passive latching cable available
Component Type		Receptacle
Electrical Model		Yes
Overview		iPass™ Connector System
Product Name		iPass™, Mini Multi-Lane, PCI Express*
Type		N/A
UPC		822350092685
Physical		
Circuits (Loaded)		68
Circuits (maximum)		68
Color - Resin		Black
Durability (mating cycles max)		50
Flammability		94V-0
Gender		Female
Keying to Mating Part		Yes
Lock to Mating Part		None
Material - Metal		Copper-Nickel-Zinc, High Performance Alloy (HPA)
Material - Plating Mating		Gold
Material - Plating Termination		Tin
Material - Resin		High Temperature Thermoplastic
Net Weight		4.664/g
Number of Rows		2
Orientation		Right Angle
PC Tail Length		1.96mm
PCB Locator		Yes
PCB Retention		Yes
PCB Thickness - Recommended		1.57mm
Packaging Type		Embossed Tape on Reel
Panel Mount		No
Pitch - Mating Interface		0.80mm
Pitch - Termination Interface		0.80mm
Plating min - Mating		0.381μm
Plating min - Termination		2.540μm
Polarized to Mating Part		Yes
Ports		1
Surface Mount Compatible (SMC)		Yes
Temperature Range - Operating		-40°C to +80°C

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Contains SVHC(2014 December 17): No

Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

ELV

China RoHS

Green Image

Not Relevant

Search Parts in this Series

75783 Series

Use With

iPass™ Cable Assemblies, 79575 , 79576 , 74562 , 74563 , 79536 , 74573 ,

Termination Interface: Style	Surface Mount, Through Hole
Waterproof / Dustproof	No
Wire Insulation Diameter	N/A
Wire Size AWG	N/A
Electrical	
Current - Maximum per Contact	0.5A
Grounding to Panel	None
Voltage - Maximum	30V AC (RMS)/DC
Solder Process Data	
Lead-freeProcess Capability	REFLOW
Process Temperature max. C	260
Material Info	
Reference - Drawing Numbers	
Application Specification	AS-75783-001
Electrical Model Document	EE-75586-001
Product Specification	PS-75783-001
S-Parameter Model	SP-75586-001
Sales Drawing	SD-75783-001

This document was generated on 07/01/2015

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION