

PRODUCT DATASHEET

Leila series

last update 10/4/2014

DETAILS

Product Number	CP11631_LXP3-RS
Family	Leila
Type	Assembly
Color	white
Diameter	21.6 mm
Height	14.7 mm
Style	round
Optic Material	PMMA
Holder Material	PC
Fastening	glue
Status	ready
ROHS Comliant	Yes
Date Updated	10/04/2014

OPTICAL PROPERTIES

	Viewing	Light	Effi-		
LED	Angle	Beam	ciency	cd/lm	Connector
Z5	sim: 10	Real spot	94 %	-	-
XP-E	7 deg	Real spot	94 %	36.000	-
XP-L HI	9 deg	Real spot	93 %	21.000	-
XP-G	10 deg	Real spot	92 %	16.500	-

H

G

F

E

D

C

B

A

4

3

2


1

4


3

2


1



Front view
Scale: 3:1




Isometric view
Scale: 3:1



Bottom view
Scale: 3:1

INDEX	PART NO	MATERIAL	COLOUR
1	Lens	PMMA 8N	
2	Holder	PC Makrolon 2407	white

Tolerances if not otherwise shown According to DIN ISO 2768-1 Linear measures: Up to 30mm class M, otherwise class C. According to DIN ISO 2768-2 Form and position: class L	
THIRD ANGLE PROJECTION:	
This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.	

		LediL Oy Salorankatu 10 FIN 24240 SALO Finland	
DRAWING TITLE			
Datasheet_LXP3-Series			
SIZE	PART NUMBER		
A3	Datasheet		
SCALE	3:1	WEIGHT	7,49 g
			SHEET 1/1


H

G

B

A


Luminaire: Ledil Oy CP11631_LXP3-RS-XP-E CP11631_LXP3-RS-XP-E
Lamps: 1 x Cree XP-E (White)




Ledil CP11631_LXP3-RS_(XP-L_HI) / LDC (Linear)

Luminaire: Ledil CP11631_LXP3-RS_(XP-L_HI)

Lamps: 1 x CREE_XP-L_HI_116.97lm@250mA_P=0.75W_I=0.25A




Luminaire: Ledil Oy CP11631_LXP3-RS-XP-E CP11631_LXP3-RS-XP-E
Lamps: 1 x Cree XP-E (White)



Ledil CP11631_LXP3-RS_(XP-L_HI) / LDC (Polar)

Luminaire: Ledil CP11631_LXP3-RS_(XP-L_HI)

Lamps: 1 x CREE_XP-L_HI_116.97lm@250mA_P=0.75W_I=0.25A



cd/klm

— C0 - C180

— C90 - C270

$\eta = 93\%$

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.

GENERAL INFORMATION

- Product series especially designed & optimized for series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Fastening to PCB with appropriate adhesive. By clicking link below you can find Ledil recommended glue options.
http://www.ledil.com/datasheets/DataSheet_GLUES.pdf

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit board weaken the strength of the glue.

NOTE 2: All surfaces where glue is applied must be clean, dry and free from grease and dirt. If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer -this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.

Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.