

NL17SZ17

Single Non-Inverting Buffer with Schmitt Trigger

The NL17SZ17 is a single Non-inverting Schmitt Trigger Buffer in three tiny footprint packages. The device performs much as LCX multi-gate products in speed and drive.

Features

- Tiny SOT-353, SOT-553 and SOT-953 Packages
- Source/Sink 24 mA at 3.0 Volts
- Chip Complexity: FETs = 20
- Designed for 1.65 V to 5.5 V V_{CC} Operation
- NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant




Figure 1. Pinout (Top View)




Figure 2. Logic Symbol

PIN ASSIGNMENT (SOT-353/SC70-5/SC-88A/SOT-553)

| Pin | Function |
|-----|----------|
| 1 | NC |
| 2 | A |
| 3 | GND |
| 4 | Y |
| 5 | V_{CC} |

PIN ASSIGNMENT (SOT-953)

| Pin | Function |
|-----|----------|
| 1 | IN A |
| 2 | GND |
| 3 | NC |
| 4 | Y |
| 5 | V_{CC} |

FUNCTION TABLE


| Input | Output |
|-------|--------|
| A | Y |
| L | L |
| H | H |



ON Semiconductor®

www.onsemi.com


MARKING DIAGRAMS



LX = Specific Device Code
M = Date Code*
▪ = Pb-Free Package

(Note: Microdot may be in either location)

*Date Code orientation and/or position may vary depending upon manufacturing location.



A = Specific Device Code
(A with 90 degree clockwise rotation)
M = Month Code

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

NL17SZ17

MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit |
|----------------------|--|---|---------------------------|
| V _{CC} | DC Supply Voltage | -0.5 to +7.0 | V |
| V _I | DC Input Voltage | -0.5 ≤ V _I ≤ +7.0 | V |
| V _O | DC Output Voltage (SOT-353/SC70-5/SC-88A/SOT-553 Packages) | Output in High or LOW State (Note 1) Power-Down Mode | -0.5 to +7.0 |
| V _O | DC Output Voltage (SOT-953 Package) | -0.5 to V _{CC} + 0.5 | V |
| I _{IK} | DC Input Diode Current V _I < GND | -50 | mA |
| I _{OK} | DC Output Diode Current (SOT-953 Package) | V _O < GND, V _O > V _{CC} | ±50 |
| I _{OK} | DC Output Diode Current (SOT-353/SC70-5/SC-88A/SOT-553 Packages) | V _O < GND | -50 |
| I _O | DC Output Sink Current | ±50 | mA |
| I _{CC} | DC Supply Current per Supply Pin | ±100 | mA |
| I _{GND} | DC Ground Current per Ground Pin | ±100 | mA |
| T _{STG} | Storage Temperature Range | -65 to +150 | °C |
| T _L | Lead Temperature, 1 mm from Case for 10 Seconds | 260 | °C |
| T _J | Junction Temperature under Bias | +150 | °C |
| θ _{JA} | Thermal Resistance | SOT-353 (Note 2) SOT-553 | 350 496 |
| P _D | Power Dissipation in Still Air at 85°C | SOT-353 SOT-553 | 186 135 |
| MSL | Moisture Sensitivity | | Level 1 |
| F _R | Flammability Rating | Oxygen Index: 28 to 34 | UL 94 V-0 @ 0.125 in |
| ESD | ESD Classification | Human Body Model (Note 3) Machine Model (Note 4) Charged Device Model | Class 2 Class C N/A |
| I _{Latchup} | Latchup Performance Above V _{CC} and Below GND at 85°C (Note 5) | | ±500 |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. I_O absolute maximum rating must be observed.
2. Measured with minimum pad spacing on an FR4 board, using 10 mm-by-1 inch, 2-ounce copper trace with no air flow.
3. Tested to EIA/JESD22-A114-A, rated to EIA/JESD22-A114-B.
4. Tested to EIA/JESD22-A115-A, rated to EIA/JESD22-A115-A.
5. Tested to EIA/JESD78.

RECOMMENDED OPERATING CONDITIONS

| Symbol | Parameter | Min | Max | Unit |
|-----------------|--|--|-------------|----------------------------------|
| V _{CC} | Supply Voltage | Operating Data Retention Only | 1.65 5.5 | 5.5 V |
| V _I | Input Voltage, (Note 6) | 0 | 5.5 | V |
| V _O | Output Voltage (SOT-353/SC70-5/SC-88A/SOT-553 Packages) | (HIGH or LOW State) | 0 | 5.5 |
| V _O | Output Voltage (SOT-953 Package) | (HIGH or LOW State) | 0 | V _{CC} |
| T _A | Operating Free-Air Temperature | -55 | +125 | °C |
| Δt/ΔV | Input Transition Rise or Fall Rate | V _{CC} = 2.5 V ±0.2 V V _{CC} = 3.0 V ±0.3 V V _{CC} = 5.0 V ±0.5 V | 0 0 0 | No Limit No Limit No Limit |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

6. Unused inputs may not be left open. All inputs must be tied to a high-logic voltage level or a low-logic input voltage level.

NL17SZ17

DC ELECTRICAL CHARACTERISTICS

| Symbol | Parameter | Condition | V _{CC} (V) | T _A = 25°C | | | -55°C ≤ T _A ≤ 125°C | | Units |
|------------------|---|---|------------------------|-----------------------|-----------------|------|--------------------------------|------|-------|
| | | | | Min | Typ | Max | Min | Max | |
| V _{T+} | Positive Input Threshold Voltage | | 1.65 | 0.6 | 1.0 | 1.4 | 0.6 | 1.4 | V |
| | | | 2.3 | 1.0 | 1.5 | 1.8 | 1.0 | 1.8 | |
| | | | 2.7 | 1.2 | 1.7 | 2.0 | 1.2 | 2.0 | |
| | | | 3.0 | 1.3 | 1.9 | 2.2 | 1.3 | 2.2 | |
| | | | 4.5 | 1.9 | 2.7 | 3.1 | 1.9 | 3.1 | |
| | | | 5.5 | 2.2 | 3.3 | 3.6 | 2.2 | 3.6 | |
| V _{T-} | Negative Input Threshold Voltage | | 1.65 | 0.2 | 0.5 | 0.8 | 0.2 | 0.8 | V |
| | | | 2.3 | 0.4 | 0.75 | 1.15 | 0.4 | 1.15 | |
| | | | 2.7 | 0.5 | 0.87 | 1.4 | 0.5 | 1.4 | |
| | | | 3.0 | 0.6 | 1.0 | 1.5 | 0.6 | 1.5 | |
| | | | 4.5 | 1.0 | 1.5 | 2.0 | 1.0 | 2.0 | |
| | | | 5.5 | 1.2 | 1.9 | 2.3 | 1.2 | 2.3 | |
| V _H | Input Hysteresis Voltage | | 1.65 | 0.1 | 0.48 | 0.9 | 0.1 | 0.9 | V |
| | | | 2.3 | 0.25 | 0.75 | 1.1 | 0.25 | 1.1 | |
| | | | 2.7 | 0.3 | 0.83 | 1.15 | 0.3 | 1.15 | |
| | | | 3.0 | 0.4 | 0.93 | 1.2 | 0.4 | 1.2 | |
| | | | 4.5 | 0.6 | 1.2 | 1.5 | 0.6 | 1.5 | |
| | | | 5.5 | 0.7 | 1.4 | 1.7 | 0.7 | 1.7 | |
| V _{OH} | High-Level Output Voltage V _{IN} = V _{IH} or V _{IL} | I _{OH} = -100 μA I _{OH} = -3 mA I _{OH} = -8 mA I _{OH} = -12 mA I _{OH} = -16 mA I _{OH} = -24 mA I _{OH} = -32 mA | 1.65 to 5.5 | V _{CC} - 0.1 | V _{CC} | | V _{CC} - 0.1 | | V |
| | | | 1.65 | 1.29 | 1.52 | | 1.29 | | |
| | | | 2.3 | 1.9 | 2.1 | | 1.9 | | |
| | | | 2.7 | 2.2 | 2.4 | | 2.2 | | |
| | | | 3.0 | 2.4 | 2.7 | | 2.4 | | |
| | | | 3.0 | 2.3 | 2.5 | | 2.3 | | |
| | | | 4.5 | 3.8 | 4.0 | | 3.8 | | |
| V _{OL} | Low-Level Output Voltage V _{IN} = V _{IH} or V _{IL} | I _{OL} = 100 μA I _{OL} = 3 mA I _{OL} = 8 mA I _{OL} = 12 mA I _{OL} = 16 mA I _{OL} = 24 mA I _{OL} = 32 mA | 1.65 to 5.5 | | 0.1 | | 0.1 | V | |
| | | | 1.65 | | 0.08 | 0.24 | 0.24 | | |
| | | | 2.3 | | 0.2 | 0.3 | 0.3 | | |
| | | | 2.7 | | 0.22 | 0.4 | 0.4 | | |
| | | | 3.0 | | 0.28 | 0.4 | 0.4 | | |
| | | | 3.0 | | 0.38 | 0.55 | 0.55 | | |
| | | | 4.5 | | 0.42 | 0.55 | 0.55 | | |
| I _{IN} | Input Leakage Current | V _{IN} = 5.5 V or GND | 0 to 5.5 | | ±0.1 | | ±1.0 | μA | |
| I _{OFF} | Power Off Leakage Current (SOT-353/ SC70-5/SC-88A/ SOT-553 Packages) | V _{IN} = 5.5 V or V _{OUT} = 5.5 V | 0 | | 1.0 | | 10 | μA | |
| I _{CC} | Quiescent Supply Current | V _{IN} = 5.5 V or GND | 5.5 | | 1.0 | | 10 | μA | |

AC ELECTRICAL CHARACTERISTICS (Input t_r = t_f = 3.0 ns)

| Symbol | Parameter | Condition | V _{CC} (V) | T _A = 25°C | | | -55°C ≤ T _A ≤ 125°C | | Units |
|--------------------------------------|--|--|------------------------|-----------------------|-----|------|--------------------------------|------|-------|
| | | | | Min | Typ | Max | Min | Max | |
| t _{PLH} t _{PHL} | Propagation Delay Input A to Y (Figures 3 and 4) | R _L = 1 MΩ, C _L = 15 pF | 1.65 | 2.0 | 9.1 | 15 | 2.0 | 15.6 | ns |
| | | | 1.8 | 2.0 | 7.6 | 12.5 | 2.0 | 13 | |
| | | | 2.5 ± 0.2 | 1.0 | 5.0 | 9.0 | 1.0 | 9.5 | |
| | | | 3.3 ± 0.3 | 1.0 | 3.7 | 6.3 | 1.0 | 6.5 | |
| | | | 5.0 ± 0.5 | 0.5 | 3.1 | 5.2 | 0.5 | 5.5 | |
| | | 3.3 ± 0.3 | 1.5 | 4.4 | 7.2 | 1.5 | 7.5 | | |
| | | R _L = 500 Ω, C _L = 50 pF | 5.0 ± 0.5 | 0.8 | 3.7 | 5.9 | 0.8 | 6.2 | |

CAPACITIVE CHARACTERISTICS

| Symbol | Parameter | Condition | Typical | Units |
|-----------------|---|--|---------|-------|
| C _{IN} | Input Capacitance | V _{CC} = 5.5 V, V _I = 0 V or V _{CC} | > 2.5 | pF |
| C _{PD} | Power Dissipation Capacitance (Note 7) | 10 MHz, V _{CC} = 3.3 V, V _I = 0 V or V _{CC} | 9 | pF |
| | | 10 MHz, V _{CC} = 5.5 V, V _I = 0 V or V _{CC} | 11 | |

7. C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: I_{CC(OPR)} = C_{PD} • V_{CC} • f_{in} + I_{CC}. C_{PD} is used to determine the no-load dynamic power consumption; P_D = C_{PD} • V_{CC}² • f_{in} + I_{CC} • V_{CC}.

NL17SZ17





Figure 3. Switching Waveforms



A 1 MHz square input wave is recommended for propagation delay tests.

Figure 4. Test Circuit





Figure 5. Typical Input Threshold, V_{T+} , V_{T-} versus Power Supply Voltage



(a) A Schmitt-Trigger Squares Up Inputs With Slow Rise and Fall Times

(b) A Schmitt-Trigger Offers Maximum Noise Immunity

Figure 6. Typical Schmitt-Trigger Applications

NL17SZ17

DEVICE ORDERING INFORMATION



| Device Order Number | Package Type | Tape/Reel Size† |
|---------------------|----------------------------------|--------------------------|
| NL17SZ17DFT2G | SC-88A/SC-70-5/SOT-353 (Pb-Free) | 3000 Units / Tape & Reel |
| NLV17SZ17DFT2G* | SC-88A/SC-70-5/SOT-353 (Pb-Free) | 3000 Units / Tape & Reel |
| NL17SZ17XV5T2G | SOT-553 (Pb-Free) | 4000 Units / Tape & Reel |
| NL17SZ17XV5T2GH | SOT-553 (Pb-Free) | 4000 Units / Tape & Reel |
| NL17SZ17P5T5G | SOT-953 (Pb-Free) | 8000 Units / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

*NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable.

PACKAGE DIMENSIONS

SOT-553 XV5 SUFFIX CASE 463B ISSUE B




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.

| DIM | MILLIMETERS | | | INCHES | | |
|-----|-------------|------|------|-----------|-------|-------|
| | MIN | NOM | MAX | MIN | NOM | MAX |
| A | 0.50 | 0.55 | 0.60 | 0.020 | 0.022 | 0.024 |
| b | 0.17 | 0.22 | 0.27 | 0.007 | 0.009 | 0.011 |
| c | 0.08 | 0.13 | 0.18 | 0.003 | 0.005 | 0.007 |
| D | 1.50 | 1.60 | 1.70 | 0.059 | 0.063 | 0.067 |
| E | 1.10 | 1.20 | 1.30 | 0.043 | 0.047 | 0.051 |
| e | 0.50 BSC | | | 0.020 BSC | | |
| L | 0.10 | 0.20 | 0.30 | 0.004 | 0.008 | 0.012 |
| HE | 1.50 | 1.60 | 1.70 | 0.059 | 0.063 | 0.067 |

SOLDERING FOOTPRINT*






*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NL17SZ17

PACKAGE DIMENSIONS


SC-88A (SC-70-5/SOT-353)
CASE 419A-02
ISSUE L



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.
 4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | INCHES | | MILLIMETERS | |
|-----|-----------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | 0.071 | 0.087 | 1.80 | 2.20 |
| B | 0.045 | 0.053 | 1.15 | 1.35 |
| C | 0.031 | 0.043 | 0.80 | 1.10 |
| D | 0.004 | 0.012 | 0.10 | 0.30 |
| G | 0.026 BSC | | 0.65 BSC | |
| H | --- | 0.004 | --- | 0.10 |
| J | 0.004 | 0.010 | 0.10 | 0.25 |
| K | 0.004 | 0.012 | 0.10 | 0.30 |
| N | 0.008 REF | | 0.20 REF | |
| S | 0.079 | 0.087 | 2.00 | 2.20 |

SOLDERING FOOTPRINT*






*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NL17SZ17

PACKAGE DIMENSIONS

SOT-953 CASE 527AE ISSUE E




NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF THE BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| MILLIMETERS | | | |
|-------------|-----------|------|------|
| DIM | MIN | NOM | MAX |
| A | 0.34 | 0.37 | 0.40 |
| b | 0.10 | 0.15 | 0.20 |
| C | 0.07 | 0.12 | 0.17 |
| D | 0.95 | 1.00 | 1.05 |
| E | 0.75 | 0.80 | 0.85 |
| e | 0.35 BSC | | |
| He | 0.95 | 1.00 | 1.05 |
| L | 0.175 REF | | |
| L2 | 0.05 | 0.10 | 0.15 |
| L3 | --- | --- | 0.15 |

SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and the are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marketing.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative