Chip Resistors

Style CR1

General Specifications

• Resistance: 100 Ω standard, (other Ω values available)

 Resistive Tolerance: ±5% standard (2% Available)

Operating Temp Range: -55 to +150°C
 Temperature Coefficient: <150 ppm/°C

• Resistive Elements: Proprietary Thin Film


Substrate Material: Aluminum Nitride

• Terminals: Silver

Lead-Free, RoHS Compliant
 Reliability: MIL-PRF-55342

Non-Magnetic


Tape and Reel Specifications:
 See Page 39 of the full Resistive Products Catalog




ATC	W	L	Т	Α	В	Capacitance	Power Max**
Part Number*	±.010	±.010	±.005	±.005	(Typ.)	(pF)	(Watts)
CR11005TxxxxJ	.050	.100	.025	.045	.020	.75	5W
CR11206TxxxxJ	.060	.120	.025	.055	.020	.90	15W
CR12010TxxxxJ	.100	.200	.040	.090	.020	1.0	30W
CR12525TxxxxJ	.245	.245	.040	.130	.020	2.0	60W
CR12525TxxxxJ01	.245	.245	.040	.130	.020	2.0	100W
CR13725TxxxxJ	.250	.375	.040	.198	.025	4.15	150W
CR13737TxxxxJ	.370	.370	.040	.330	.025	6.0	250W

^{*} xxxx denotes Ohm value.

Power Derating



ATC Part Number Code



Sales of ATC products are subject to the terms and conditions contained in American Technical Ceramics Corp. Terms and Conditions of Sale (ATC document #001-992 Rev. B 12/05). Copies of these terms and conditions will be provided upon request. They may also be viewed on ATC's website at www.atceramics.com/productfinder/default.asp. Click on the link for Terms and Conditions of Sale.

ATC has made every effort to have this information as accurate as possible. However, no responsibility is assumed by ATC for its use, nor for any infringements of rights of third parties which may result from its use. ATC reserves the right to revise the content or modify its product without prior notice.

© 2012 American Technical Ceramics Corp. All Rights Reserved.

Excerpt from ATC # 001-944; Rev. U, 11/14

AMERICAN TECHNICAL CERAMICS

ATC North America sales@atceramics.com

ATC Europe saleseur@atceramics.com

ATC Asia sales@atceramics-asia.com

^{**} Test Condition: Chip soldered to a large copper carrier whose surface is at 100°C; maximum rated power applied.

Specification: The resistance of the film shall change no more than 0.5% during and after a 1000-hr. Burn-in per Mil-PRF-55342.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

American Technical Ceramics (ATC):

<u>CR11005T0100JTR</u> <u>CR11206T0100JTR</u> <u>CR12010T0050JTR</u> <u>CR12525T0050JTR</u> <u>CR13725T0050JTR</u> CR13737T0050JTR